

LED SPOTLIGHT-CANLESS SMART MINI PANEL - RGB + TUNABLE WHITE 4", 6" - ROUND & SQUARE



LUXSMART
BY **LUXRITE®**



GROUP MULTIPLE LIGHTS



Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates.
Google and Google Play are trademarks of Google LLC.



ELECTRICAL

	MODEL	DESCRIPTION	POWER	INPUT VOLTS	EFFICACY	LIFETIME	BEAM ANGLE	COST/YR
RD	LR22740	LED/SMP4/RGB/CCT/RD	10.5	120V	64	50,000	180°	\$ 1.26
SQ	LR22742	LED/SMP4/RGB/CCT/SQ	10.5	120V	64	50,000	180°	\$ 1.26
RD	LR22745	LED/SMP6/RGB/CCT/RD	13	120V	77	50,000	180°	\$ 1.56
SQ	LR22748	LED/SMP6/RGB/CCT/SQ	13	120V	77	50,000	180°	\$ 1.56

PHOTOMETRIC

MODEL	DESCRIPTION	COLOR (CCT)	TEMP	LUMEN	CRI	ETL	ENERGY STAR	PLATE (KNOCKOUT)
LR22740	LED/SMP4/RGB/CCT/RD	RGBW 2000-5000K	RGB + TUNABLE WHITE	700	90	YES	YES	LR41002 (#1)
LR22742	LED/SMP4/RGB/CCT/SQ	RGBW 2000-5000K	RGB + TUNABLE WHITE	700	90	YES	YES	LR41002 (#1)
LR22745	LED/SMP6/RGB/CCT/RD	RGBW 2000-5000K	RGB + TUNABLE WHITE	1000	90	YES	YES	LR41002 (#2)
LR22748	LED/SMP6/RGB/CCT/SQ	RGBW 2000-5000K	RGB + TUNABLE WHITE	1000	90	YES	YES	LR41002 (#2)

COMPATIBLE WITH:

LR35126
Emergency LED Driver



LR41002
New Construction Mounting Plate



KNOCKOUT SIZE

#0	Ø3.14" (Ø80 mm)
#1	Ø4.33" (Ø110 mm)
#2	Ø6.29" (Ø160 mm)

DIMENSIONS

