NQ30L1C

Panelboard interior, NQ, main lugs, 100A, Cu bus, 30 pole spaces, 1 phase, 3 wire, 240VAC, 48VDC





Main

IVIAIII	
Panelboard Type	Main lugs
Product or Component Type	Interiors
Branch Circuit Breaker Type	QOB QOB-VH QHB
Busbar Material	Copper

Complementary

Number of spaces	30
Enclosure Nominal Height	32 in (812.80 mm)
Enclosure Nominal Width	20 in (508.00 mm)
Enclosure Nominal Depth	5.75 In (146.05 mm) NEMA 1 6.5 in (165.10 mm) NEMA 3R/5/12
Line Rated Current	100 A
[lu] rated interrupted current	10 KA 22 KA 65 kA
Wiring configuration	3-wire
Number of Phases	1 phase
Voltage Rating	240 V AC 48 V DC
Tightening torque	40.0150.01 Lbf.In (4.525.65 N.m) 0.020.10 in² (13.3067.43 mm²) (AWG 6AWG 2/0) 100.01 Lbf.In (11.3 N.m) 0.020.10 in² (13.3067.43 mm²) (AWG 6AWG 2/0) 274.99 Lbf.In (31.07 N.m) 0.020.27 in² (13.30177.3 mm²) (AWG 6350 kcmil) 274.99 Lbf.In (31.07 N.m) 0.020.20 in² (13.30126.7 mm²) (AWG 6250 kcmil) 274.99 lbf.in (31.07 N.m) 0.170.24 in² (107.2152 mm²) (AWG 4300 kcmil)
Height	27 in (685.80 mm)
Width	10.44 in (265.18 mm)

Environment

Standards	UL 67
	CSA C22.2

Ordering and shipping details

Category	09151-NQ RTA PANELBOARDS
Discount Schedule	PE1A
GTIN	785901507925
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.30 in (16.0 cm)
Package 1 Width	13.90 in (35.3 cm)
Package 1 Length	31.89 in (81.0 cm)
Package 1 Weight	16.38 lb(US) (7.43 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

	•
Warranty	18 months