# QO816L100F

Load center, QO, 1 phase, 8 spaces, 16 circuits, 100A fixed main lugs, NEMA1, flush cover, UL





#### Main

Marketing Trade Name	QO
Product Type	Load Center
Cover Type	Flush cover

Complementary

Complementary		
Tightening Torque	Main lugs 50 lb.in, AWG 8, aluminium/copper Main lugs 50 lb.in, AWG 6AWG 1/0, aluminium/copper	
PoN Convertible Mains (lugs)	Fixed Mains (lugs)	
Rated Current	100 A	
Number of Spaces	8	
Max Short Circuit Current Rating	10 kA	
Maximum Number of Single Pole Circuits	16	
Maximum Number of Tandem Breakers	8	
Number of Phases	1 phase	
Voltage Rating	120/240 V AC	
Wire Size	AWG 8AWG 1 aluminium/copper	
Ground Bar	Grounding bar (ordered separately)	
Electrical Connection	Lugs	
Wiring Configuration	3-wire	
Busbar Material	Tin plated aluminium busbar	
Enclosure Material	Welded sheet steel	
Surface Finish	Baked enamel Gray	
Box Number	4	
Height	12.56 in (319 mm)	
Width	8.90 in (226 mm)	

### Environment

Enclosure Rating	NEMA 1 indoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

#### Ordering and shipping details

and an analysis of the second		
00101-QO 1PH LC,2-8CKT,NEMA 1,3R		
DE3A		
785901785675		
Yes		
MX		

## Packing Units

<b>3</b>	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.21 in (10.7 cm)
Package 1 Width	10.79 in (27.4 cm)
Package 1 Length	14.49 in (36.8 cm)
Package 1 Weight	7.83 lb(US) (3.55 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	78
Package 2 Height	35.00 in (88.9 cm)
Package 2 Width	43.00 in (109.22 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	633.57 lb(US) (287.382 kg)

## Offer Sustainability

Green Premium product
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
☑ REACh Declaration
Compliant EEU RoHS Declaration
Yes
₫ <sub>Yes</sub>
☑ China RoHS Declaration

### Contractual warranty

Warranty	18 months