## **D222N**

Safety switch, general duty, fusible, 60A, 2 pole, 15hp, 240VAC, NEMA 1, 3 wire, 1 neutral,





#### Main

Product	Single Throw Safety Switch	
Duty Rating	General duty	
Device Application	Residential	
Disconnect Type	Fusible disconnect switch	
Factory Installed Neutral	Neutral (factory installed)	
Phase	1 phase	
Number of Poles	2	
Current Rating	60 A	
Voltage Rating	240 V AC	
Enclosure Rating NEMA	NEMA 1	
Motor power hp	1.5 Hp at 120 V AC 60 Hz for 1 phase motors 3 Hp at 120 V AC 60 Hz for 3 phase motors 3 Hp at 240 V AC 60 Hz for 1 phase motors 7.5 Hp at 240 V AC 60 Hz for 3 phase motors 10 Hp at 240 V AC 60 Hz for 1 phase motors 15 hp at 240 V AC 60 Hz for 3 phase motors	

### Complementary

Short Circuit Current Rating	100 kA maximum depending on fuse H, K or R		
Fuse type	H, K or R		
Mounting Type	Surface		
Electrical Connection	Lugs		
Wiring configuration	3-wire		
Wire Size	AWG 12AWG 3 aluminium AWG 14AWG 3 copper		
Tightening torque	35 Lbf.In (3.95 N.m) 0.000.01 in² (2.085.26 mm²) (AWG 14AWG 10) 45 Lbf.In (5.08 N.m) 0.01 in² (8.37 mm²) (AWG 8) 35 Lbf.In (3.95 N.m) (AWG 14AWG 10) 45 Lbf.In (5.08 N.m) 0.020.03 in² (12.321.12 mm²) (AWG 6AWG 4) 50 lbf.in (5.65 N.m) 0.04 in² (26.67 mm²) (AWG 3)		
Depth	4.87 in (123.70 mm)		
Width	7.45 in (189.23 mm)		
Height	14.88 in (377.95 mm)		
Net Weight	8.82 lb(US) (4 kg)		

#### Environment

O (CC C	1. J.Cl., E0075
Certifications UL lis	ited file E28/5
	ited file E2073

### Ordering and shipping details

US1DE1A00006	
DE1A	
785901460626	
Yes	
US	
_	DE1A 785901460626 Yes

# Packing Units

<b>3</b>	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.00 in (12.7 cm)
Package 1 Width	7.60 in (19.304 cm)
Package 1 Length	16.00 in (40.64 cm)
Package 1 Weight	7.77 lb(US) (3.524 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	105
Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	816.73 lb(US) (370.464 kg)

# Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
PVC free	Yes	

## Contractual warranty

Warranty	18 months	