PRODUCT DETAILS

WALLCOVERING PANELS

WALLOOVERING PANELS					
PATTERN:	AGATE	15.			
COLORWAY:	LAVENDER AMETHYST				
SKU:	AG05				
SUBSTRATE:	COMMERCIAL TYPE II MYLAR/VINYL RESIDENTIAL AVAILABLE	, 2 ₁			
PANEL LENGTHS:	9'H / 12'H / 15'H LONGER AVAILABLE				
REPEAT:	52" X 52"	in the second se			
MATERIAL WIDTH:	54" UNTRIMMED				
STRAIGHT MATCH					
½" BLEED + ½" SELVAGE					
DIGITAL PRINT					
REFER TO SAMPLE FOR ACCURATE COLOR.					
PRINT TO ORDER. SLIGHT COLOR VARIATIONS BETWEEN PRINT RUNS.					

54" (UNTRIMMED)

TYPE II MYLAR/VINYL SUBSTRATE SPECS.

COMMERCIAL

GENERAL LAST UPDATED: 11/28/201		
DESCRIPTION	COMMERCIAL GRADE, WIDE-FORMAT WALLCOVERING MEDIA	
CONSTRUCTION	MULTI-PLY VINYL/MYLAR CONSTRUCTION WITH NON-WOVEN BACKING	
MATERIAL WIDTH		54"
WEIGHT	TOTAL: POLYESTER/VINYL WEIGHT: FABRIC WEIGHT: ADHESIVE:	20 OZ / LINEAL YARD 16.8 OZ / LINEAL YARD 2.7 OZ / LINEAL YARD 0.5 OZ / LINEAL YARD
THICKNESS		17 MIL.
APPLICATION	STANDARD COMMERCIAL WALLCOVERING PASTES, PRIMERS AND TECHNIQUES	
AFFLICATION	FOR INDOOR USE IN ENVIR	RONMENTALLY CONTROLLED SPACES

TESTS / CERTIFICATIONS / QUALITIES				
FEDERAL SPECIFICATION		CCC-408-D TYPE II CLASS A		
WA SPECIFICATION		W-101 TYPE II		
	MEETS OR EXCEEDS REQUIREMENTS FOR FLAME SPREAD, SMOKE DEVELOPED AND FLASHOVER.			
FIRE TEST RATING	ASTM-E84 TUNNEL TEST NFPA LIFE SAFETY CODE 101 EU CLASS FLAME (EN 15102) CAN/ULC S102	CLASS A CLASS A PASSED CLASS B, S2 PASSED ALL REQUIREMENTS		
MOLD/MILDEW RESISTANCE	ASTM-G21 SPECIFICATION	S, PASSED ALL REQUIREMENTS		
INDOOR AIR QUALITY	MANUFACTURED WITH LOW VOC VINYL CALIFORNIA CDPH STANDARD FOR SCHOOLS + OFFICES TESTED PER CA-1350 WA CERTIFIED NSF/ANSI 342 SUSTAINABILITY STANDARD			
		ACTURED WITHOUT THE USE OF OMINATED FLAME RETARDANTS		
ADDITIONAL NOTES	MEETS OR EXCEEDS EU TOXICITY STANDARD EN12149 A, B, C FOR HEAVY METALS AND FORMALDEHYDE			
		VOVEN BACKING CONTAINS 50% ONSUMER RECYCLED CONTENT		