PRODUCT DETAILS

WALLCOVERING PANELS

WALLCOVERING PANELS				
PATTERN:	DREAMHOUSE	15'		
COLORWAY:	AMELIA			
ITEM #:	DH04			
SUBSTRATE:	COMMERCIAL TYPE II VINYL RESIDENTIAL AVAILABLE	15,		
PANEL	9'H / 12'H / 15'H			
LENGTHS:	LONGER AVAILABLE			
REPEAT:	52"W X 55"H			
MATERIAL	54"			
WIDTH:	UNTRIMMED			
STRAIGHT MATCH				
½" BLEED + ½" SELVAGE				
DIGITAL PRINT				
REFER TO SAMPLE FOR ACCURATE COLOR.				
PRINT TO	O ORDER. SLIGHT COLOR			
	NS BETWEEN PRINT RUNS.			
NOTES:				
		54" (UNTRIMMED)		

TYPE II VINYL SUBSTRATE SPECS.

COMMERCIAL

GENERAL		LAST UPDATED: 11/28/2018	
DESCRIPTION	COMMERCIAL GRADE, WIDE-FOR	COMMERCIAL GRADE, WIDE-FORMAT WALLCOVERING MEDIA	
CONSTRUCTION	2-PLY EMBOSSED VINYL FACE/LAMINATED FABRIC BACKING		
MATERIAL WIDTH		54"	
WEIGHT	TOTAL: POLYESTER/VINYL WEIGHT: FABRIC WEIGHT: ADHESIVE:	20 OZ / LINEAL YARD 17 OZ / LINEAL YARD 2.7 OZ / LINEAL YARD 0.3 OZ / LINEAL YARD	
THICKNESS		0.017 TO 0.027 IN	
APPLICATION	STANDARD COMMERCIAL WALLCOVERING PASTES, PRIMERS AND TECHNIQUES		
AFFLIGATION	FOR INDOOR USE IN ENVIRONMENTALLY CONTROLLED SPACES		

TESTS / CERTIFICATIONS / QUALITIES					
FEDERAL SPECIFICATION	CCC-408-D TYPE II CLASS A				
WA SPECIFICATION	W-101 TYPE II, NSF/ANSI 342 SUSTAINABILITY STANDARD				
	MEETS OR EXCEEDS REQUIRE SPREAD, SMOKE DEVELOPE				
FIRE TEST RATING	BS476 PARTS 6 AND 7 PASSED A	CLASS A CLASS A SSSED CLASS B, S2 LL REQUIREMENTS LL REQUIREMENTS			
MOLD/MILDEW RESISTANCE	ASTM-G21 SPECIFICATIONS, PASSED ALL REQUIREMENTS				
INDOOR AIR QUALITY	MANUFACTURED WITH LOW VOC VINYL CALIFORNIA CDPH STANDARD FOR SCHOOLS + OFFICES TESTED PER CA-1350 WA CERTIFIED NSF/ANSI 342 SUSTAINABILITY STANDARD				
	MANUFACTURED WIT BROMINATED FL	HOUT THE USE OF AME RETARDANTS			
ADDITIONAL NOTES	MEETS OR EXCEEDS EU TOXICITY S A, B, C FOR HEAVY METALS AN				
ADDITIONAL NOTES	NON-WOVEN BACKI POST-CONSUMER RE				
	NSF-342 CERTIFIED FOR SILVER 200Z WALLCOVERING				