PRODUCT DETAILS

WALLCOVERING PANELS

	WALLOOVEI	
PATTERN:	DREAMHOUSE	
COLORWAY:	MONIE	
ITEM #:	DH08	
SUBSTRATE:	COMMERCIAL TYPE II VINYL RESIDENTIAL AVAILABLE	
PANEL	9'H / 12'H / 15'H	
LENGTHS:	LONGER AVAILABLE	
REPEAT:	52"W X 55"H	
MATERIAL	54"	
WIDTH:	UNTRIMMED	
STRAIGHT MATCH		
½" BLEED + ½" SELVAGE		
DIGITAL PRINT		
REFER TO SAMPLE FOR ACCURATE COLOR.		
PRINT TO ORDER. SLIGHT COLOR VARIATIONS BETWEEN PRINT RUNS.		
NOTES:		



54" (UNTRIMMED)

TYPE II VINYL SUBSTRATE SPECS.

COMMERCIAL

GENERAL	LAST UPDATED: 11/28/2018		
DESCRIPTION	COMMERCIAL GRADE, WIDE-FORMAT WALLCOVERING MEDIA		
CONSTRUCTION	2-PLY EMBOSSED VINYL FACE/LAMINATED FABRIC BACKING		
MATERIAL WIDTH		54"	
WEIGHT	TOTAL: POLYESTER/VINYL WEIGHT: FABRIC WEIGHT: ADHESIVE:	20 OZ / LINEAL YARD 17 OZ / LINEAL YARD 2.7 OZ / LINEAL YARD 0.3 OZ / LINEAL YARD	
THICKNESS		0.017 TO 0.027 IN	
APPLICATION	STANDARD COMMERCIAL WALLC	STANDARD COMMERCIAL WALLCOVERING PASTES, PRIMERS AND TECHNIQUES	
	FOR INDOOR USE IN ENVIRONMENTALLY CONTROLLED SPACES		

TESTS / CERTIFICATIONS / QUALITIES		
FEDERAL SPECIFICATION	CCC-408-D TYPE II CLASS A	
WA SPECIFICATION	W-101 TYPE II, NSF/ANSI 342 SUSTAINABILITY STANDARD	
	MEETS OR EXCEEDS REQUIREMENTS FOR FLAME SPREAD, SMOKE DEVELOPED AND FLASHOVER	
FIRE TEST RATING	ASTM-E84 TUNNEL TEST CLASS A NFPA LIFE SAFETY CODE 101 CLASS A EU CLASS FLAME (EN 15102) BS476 PARTS 6 AND 7 PASSED ALL REQUIREMENTS CAN/ULC S102 PASSED ALL REQUIREMENTS	
MOLD/MILDEW RESISTANCE	ASTM-G21 SPECIFICATIONS, PASSED ALL REQUIREMENTS	
INDOOR AIR QUALITY	MANUFACTURED WITH LOW VOC VINYL CALIFORNIA CDPH STANDARD FOR SCHOOLS + OFFICES TESTED PER CA-1350 WA CERTIFIED NSF/ANSI 342 SUSTAINABILITY STANDARD	
ADDITIONAL NOTES	MANUFACTURED WITHOUT THE USE OF BROMINATED FLAME RETARDANTS	
	MEETS OR EXCEEDS EU TOXICITY STANDARD EN12149 A, B, C FOR HEAVY METALS AND FORMALDEHYDE	
	NON-WOVEN BACKING CONTAINS 50% POST-CONSUMER RECYCLED CONTENT.	
	NSF-342 CERTIFIED FOR SILVER COMPLIANCE FOR 20OZ WALLCOVERING CONSTRUCTIONS	