PRODUCT DETAILS

WALLCOVERING PANELS

	UNLEE OF VEILIN		
PATTERN:	FLORENCE		
COLORWAY:	CONSTANCE		
ITEM #:	FL01		
SUBSTRATE:	COMMERCIAL TYPE II MYLAR/VINYL RESIDENTIAL AVAILABLE		
PANEL LENGTHS:	9'H / 12'H / 15'H LONGER AVAILABLE		
REPEAT:	52"W X 26"H		
MATERIAL WIDTH:	54" UNTRIMMED		
STRAIGHT MATCH			
1/2" BLEED + 1/2" SELVAGE			
DIGITAL PRINT			
REFER TO SA	MPLE FOR ACCURATE COLOR.		
PRINT TO ORDER. SLIGHT COLOR VARIATIONS BETWEEN PRINT RUNS.			
NOTES:			



TYPE II MYLAR/VINYL SUBSTRATE SPECS.

COMMERCIAL

GENERAL	LAST UPDATED: 11/28/2018	
DESCRIPTION	COMMERCIAL GRADE, WIDE-FORMAT WALLCOVERING MEDIA	
CONSTRUCTION	MULTI-PLY VINYL/MYLAR CONSTRUCTION WITH NON-WOVEN BACKING	
MATERIAL WIDTH		54"
WEIGHT	TOTAL: POLYESTER/VINYL WEIGHT: FABRIC WEIGHT: ADHESIVE:	20 OZ / LINEAL YARD 16.8 OZ / LINEAL YARD 2.7 OZ / LINEAL YARD 0.5 OZ / LINEAL YARD
THICKNESS		17 MIL.
APPLICATION	STANDARD COMMERCIAL WALLCOVERING PASTES, PRIMERS AND TECHNIQUES	
	FOR INDOOR USE IN ENVIRONMENTALLY CONTROLLED SPACES	

TESTS / CERTIFICATIONS / QUALITIES				
FEDERAL SPECIFICATION	CCC-408-D TYPE II CLASS A			
WA SPECIFICATION	W-101 TYPE II			
	MEETS OR EXCEEDS REQUIREMENTS FOR FLAME SPREAD, SMOKE DEVELOPED AND FLASHOVER.			
FIRE TEST RATING	ASTM-E84 TUNNEL TEST NFPA LIFE SAFETY CODE 101 EU CLASS FLAME (EN 15102) CAN/ULC S102	CLASS A CLASS A PASSED CLASS B, S2 PASSED ALL REQUIREMENTS		
MOLD/MILDEW RESISTANCE	ASTM-G21 SPECIFICATIONS, PASSED ALL REQUIREMENTS			
INDOOR AIR QUALITY	MANUFACTURED WITH LOW VOC VINYL CALIFORNIA CDPH STANDARD FOR SCHOOLS + OFFICES TESTED PER CA-1350 WA CERTIFIED NSF/ANSI 342 SUSTAINABILITY STANDARD			
		CTURED WITHOUT THE USE OF OMINATED FLAME RETARDANTS		
ADDITIONAL NOTES		J TOXICITY STANDARD EN12149 Y METALS AND FORMALDEHYDE		
		OVEN BACKING CONTAINS 50%		