

# HIGH-USE / TYPE II GUIDE

LAST UPDATED: 06/01/2023

## OUR PRODUCTS

MANY OF OUR PATTERNS COME ON TYPE II VINYL BY DEFAULT.  
THIS WILL BE SPECIFIED ON THE MEMO.

WHEN DURABILITY IS REQUIRED, ALL NON-TYPE II PATTERNS MAY BE PRINTED ON THE  
FOLLOWING THREE SUBSTRATE OPTIONS AS A CUSTOM ORDER.

## DURABLE SUBSTRATE OPTIONS

<p>PERFORMANCE NON- WOVEN <i>COVERS 51" W PER A PANEL</i></p>	<p>RESIDENTIAL ALTERNATIVE TO TYPE II COMMERCIAL PAPER</p> <ul style="list-style-type: none"><li>• SUITABLE FOR LOW TRAFFIC COMMERCIAL AREAS AND HIGH TRAFFIC RESIDENTIAL AREAS<ul style="list-style-type: none"><li>- (IE: HALLWAYS, BATHROOMS, PLAYROOMS)</li></ul></li><li>• DURABLE AND WIPEABLE / WATER- RESISTANT</li><li>• STANDARD NON-WOVEN WALL ADHESIVES AND INSTALLATION TECHNIQUES</li><li>• EASY TO REMOVE. STRIPPABLE WITH MINIMUM EFFORT</li><li>• FIRE-RATED: CLASS A ASTM-E84</li><li>• THICKNESS: 13.0 MIL / WEIGHT: 200 G/M</li></ul>
<p>PVC-FREE TYPE II PAPER <i>COVERS 51" W PER A PANEL</i></p>	<p>ECO-FRIENDLY COMMERCIAL ALTERNATIVE TO TYPE II VINYL</p> <ul style="list-style-type: none"><li>• SUITABLE FOR HIGH TRAFFIC COMMERCIAL AND RESIDENTIAL AREAS</li><li>• DURABLE AND WIPEABLE / WATER- RESISTANT</li><li>• HIGHLY MOLD + MILDEW RESISTANT</li><li>• FSC CERTIFIED RESPONSIBLE USE OF FOREST RESOURCES</li><li>• CAN SUPPORT LEED CREDITS</li><li>• COMPLIANT WITH CHPS SECTION 01350 SPECIFICATION</li><li>• FIRE-RATED: CLASS A ASTM-E84</li><li>• THICKNESS: 17.0 MIL / WEIGHT: 290 G/M</li></ul>
<p>TYPE II VINYL <i>COVERS 52" W PER A PANEL</i></p>	<p>COMMERCIAL GRADE, WIDE-FORMAT WALLCOVERING MEDIA</p> <ul style="list-style-type: none"><li>• SUITABLE FOR HIGH TRAFFIC COMMERCIAL AND RESIDENTIAL AREAS</li><li>• DURABLE AND WIPEABLE / WATER- RESISTANT</li><li>• FIRE-RATED: CLASS A ASTM-E84</li><li>• THICKNESS: 17.0 MIL / WEIGHT: 20 OZ / LINEAL YARD</li></ul>