


# PRODUCT DETAILS

## WALLCOVERING PANELS

PATTERN:	GEODE
COLORWAY:	AMETHYST
ITEM #:	GD04
SUBSTRATE:	COMMERCIAL TYPE II MYLAR/VINYL
PANEL LENGTHS:	9'H / 12'H / 15'H <i>LONGER AVAILABLE</i>
REPEAT:	52"W X 39"H
MATERIAL WIDTH:	54" <i>UNTRIMMED</i>
LEAD TIME:	6-8 WEEKS TO SHIP
STRAIGHT MATCH	
½" BLEED + ½" SELVAGE	
DIGITAL PRINT	
REFER TO SAMPLE FOR ACCURATE COLOR.	
PRINT TO ORDER. SLIGHT COLOR VARIATIONS BETWEEN PRINT RUNS.	



54" (UNTRIMMED)

# TYPE II MYLAR/VINYL SUBSTRATE SPECS.

COMMERCIAL

GENERAL		LAST UPDATED: 11/28/2018
DESCRIPTION	COMMERCIAL GRADE, WIDE-FORMAT WALLCOVERING MEDIA	
CONSTRUCTION	MULTI-PLY VINYL/MYLAR CONSTRUCTION WITH NON-WOVEN BACKING	
MATERIAL WIDTH	54"	
WEIGHT	TOTAL: POLYESTER/VINYL WEIGHT: FABRIC WEIGHT: ADHESIVE:	20 OZ / LINEAL YARD 16.8 OZ / LINEAL YARD 2.7 OZ / LINEAL YARD 0.5 OZ / LINEAL YARD
THICKNESS	17 MIL.	
APPLICATION	STANDARD COMMERCIAL WALLCOVERING PASTES, PRIMERS AND TECHNIQUES  FOR INDOOR USE IN ENVIRONMENTALLY CONTROLLED SPACES	

TESTS / CERTIFICATIONS / QUALITIES		
FEDERAL SPECIFICATION	CCC-408-D TYPE II CLASS A	
WA SPECIFICATION	W-101 TYPE II	
FIRE TEST RATING	MEETS OR EXCEEDS REQUIREMENTS FOR FLAME SPREAD, SMOKE DEVELOPED AND FLASHOVER.  ASTM-E84 TUNNEL TEST NFPA LIFE SAFETY CODE 101 EU CLASS FLAME (EN 15102) CAN/ULC S102	CLASS A CLASS A PASSED CLASS B, S2 PASSED ALL REQUIREMENTS
MOLD/MILDEW RESISTANCE	ASTM-G21 SPECIFICATIONS, PASSED ALL REQUIREMENTS	
INDOOR AIR QUALITY	MANUFACTURED WITH LOW VOC VINYL CALIFORNIA CDPH STANDARD FOR SCHOOLS + OFFICES TESTED PER CA-1350 WA CERTIFIED NSF/ANSI 342 SUSTAINABILITY STANDARD	
ADDITIONAL NOTES	MANUFACTURED WITHOUT THE USE OF BROMINATED FLAME RETARDANTS  MEETS OR EXCEEDS EU TOXICITY STANDARD EN12149 A, B, C FOR HEAVY METALS AND FORMALDEHYDE  NON-WOVEN BACKING CONTAINS 50% POST-CONSUMER RECYCLED CONTENT	