## PRODUCT DETAILS

WALLCOVERING PANELS

| PATTERN:   | GEODE                             |  |
|--|-----------------------------------|--|
| COLORWAY:  | VIRIDI                            |  |
| ITEM #:  | GD05                              |  |
| SUBSTRATE:   | COMMERCIAL<br>TYPE II MYLAR/VINYL |  |
| PANEL  | 9'H / 12'H / 15'H                 |  |
| LENGTHS:   | LONGER AVAILABLE                  |  |
| REPEAT:  | 52"W X 39"H                       |  |
| MATERIAL   | 54"                               |  |
| WIDTH:   | UNTRIMMED                         |  |
| LEAD TIME:   | 6-8 WEEKS TO SHIP                 |  |
| STRAIGHT MATCH   |                                   |  |
| 1/2" BLEED + 1/2" SELVAGE                                      |                                   |  |
| DIGITAL PRINT  |                                   |  |
| REFER TO SAMPLE FOR ACCURATE COLOR.                            |                                   |  |
| PRINT TO ORDER. SLIGHT COLOR<br>VARIATIONS BETWEEN PRINT RUNS. |                                   |  |
|  |                                   |  |



WWW.FAYEBELL.COM | INFO@FAYEBELL.COM | ATLANTA, GA

## TYPE II MYLAR/VINYL SUBSTRATE SPECS.

COMMERCIAL

| GENERAL        | LAST UPDATED: 11/28/2018   |  |
|----------------|--|--|
| DESCRIPTION    | COMMERCIAL GRADE, WIDE-FORMAT WALLCOVERING MEDIA                   |  |
| CONSTRUCTION   | MULTI-PLY VINYL/MYLAR CONSTRUCTION WITH NON-WOVEN BACKING          |  |
| MATERIAL WIDTH |  | 54"  |
| WEIGHT         | TOTAL:<br>POLYESTER/VINYL WEIGHT:<br>FABRIC WEIGHT:<br>ADHESIVE:   | 20 OZ / LINEAL YARD<br>16.8 OZ / LINEAL YARD<br>2.7 OZ / LINEAL YARD<br>0.5 OZ / LINEAL YARD |
| THICKNESS      |  | 17 MIL.  |
| APPLICATION    | STANDARD COMMERCIAL WALLCOVERING PASTES, PRIMERS<br>AND TECHNIQUES |  |
|                | FOR INDOOR USE IN ENVIRONMENTALLY CONTROLLED<br>SPACES             |  |

| TESTS / CERTIFICATIONS / QUALITIES |  |   |  |  |
|------------------------------------|--|---|--|--|
| FEDERAL SPECIFICATION              | CCC-408-D TYPE II CLASS A  |   |  |  |
| WA SPECIFICATION                   | W-101 TYPE II  |   |  |  |
|                                    | MEETS OR EXCEEDS REQUIREMENTS FOR FLAME SPREAD,<br>SMOKE DEVELOPED AND FLASHOVER.  |   |  |  |
| FIRE TEST RATING                   | ASTM-E84 TUNNEL TEST<br>NFPA LIFE SAFETY CODE 101<br>EU CLASS FLAME (EN 15102)<br>CAN/ULC S102   | CLASS A<br>CLASS A<br>PASSED CLASS B, S2<br>PASSED ALL REQUIREMENTS |  |  |
| MOLD/MILDEW RESISTANCE             | ASTM-G21 SPECIFICATIONS, PASSED ALL REQUIREMENTS   |   |  |  |
| INDOOR AIR QUALITY                 | MANUFACTURED WITH LOW VOC VINYL<br>CALIFORNIA CDPH STANDARD FOR SCHOOLS + OFFICES<br>TESTED PER CA-1350<br>WA CERTIFIED NSF/ANSI 342 SUSTAINABILITY STANDARD |   |  |  |
|                                    |  | CTURED WITHOUT THE USE OF<br>OMINATED FLAME RETARDANTS              |  |  |
| ADDITIONAL NOTES                   |  | J TOXICITY STANDARD EN12149<br>Y METALS AND FORMALDEHYDE            |  |  |
|                                    |  | OVEN BACKING CONTAINS 50%   |  |  |