PRODUCT DETAILS

WALLCOVERING PANELS

WALLOOVERING TANKED					
PATTERN:	LICHEN	15.			
COLORWAY:	BIRCH				
ITEM #:	LNO1				
SUBSTRATE:	COMMERCIAL TYPE II MYLAR/VINYL RESIDENTIAL AVAILABLE	15.			
PANEL LENGTHS:	9'H / 12'H / 15'H LONGER AVAILABLE				
REPEAT:	52" X 52"				
MATERIAL WIDTH:	54" UNTRIMMED	6			
STRAIGHT MATCH					
½" BLEED + ½" SELVAGE					
DIGITAL PRINT					
REFER TO SAMPLE FOR ACCURATE COLOR.					
PRINT TO ORDER. SLIGHT COLOR VARIATIONS BETWEEN PRINT RUNS.					
NOTES:					

54" (UNTRIMMED)

TYPE II MYLAR/VINYL SUBSTRATE SPECS.

COMMERCIAL

GENERAL LAST UPDATED: 11/28/20			
DESCRIPTION	PTION COMMERCIAL GRADE, WIDE-FORMAT WALLCOVERING MEDIA		
CONSTRUCTION	MULTI-PLY VINYL/MYLAR CONSTRUCTION WITH NON-WOVEN BACKING		
MATERIAL WIDTH			
WEIGHT	TOTAL: POLYESTER/VINYL WEIGHT: FABRIC WEIGHT: ADHESIVE:	20 OZ / LINEAL YARD 16.8 OZ / LINEAL YARD 2.7 OZ / LINEAL YARD 0.5 OZ / LINEAL YARD	
THICKNESS	17 MIL.		
APPLICATION	STANDARD COMMERCIAL WALLCOVERING PASTES, PRIMERS AND TECHNIQUES		
AFFLICATION	FOR INDOOR USE IN ENVIRONMENTALLY CONTROLLED SPACES		

TESTS / CERTIFICATIONS / QUALITIES				
FEDERAL SPECIFICATION		CCC-408-D TYPE II CLASS A		
WA SPECIFICATION		W-101 TYPE II		
	MEETS OR EXCEEDS REQUIREMENTS FOR FLAME SPREAD, SMOKE DEVELOPED AND FLASHOVER.			
FIRE TEST RATING	ASTM-E84 TUNNEL TEST NFPA LIFE SAFETY CODE 101 EU CLASS FLAME (EN 15102) CAN/ULC S102	CLASS A CLASS A PASSED CLASS B, S2 PASSED ALL REQUIREMENTS		
MOLD/MILDEW RESISTANCE	ASTM-G21 SPECIFICATIONS, PASSED ALL REQUIREMENTS			
INDOOR AIR QUALITY	MANUFACTURED WITH LOW VOC VINYL CALIFORNIA CDPH STANDARD FOR SCHOOLS + OFFICES TESTED PER CA-1350 WA CERTIFIED NSF/ANSI 342 SUSTAINABILITY STANDARD			
	MANUFACTURED WITHOUT THE USE OF BROMINATED FLAME RETARDANTS			
ADDITIONAL NOTES	MEETS OR EXCEEDS EU TOXICITY STANDARD EN12149 A, B, C FOR HEAVY METALS AND FORMALDEHYDE			
		VOVEN BACKING CONTAINS 50% ONSUMER RECYCLED CONTENT		