Video/Surveillance

V300 Video Streaming Hard Drive

Stream. Record. Edit.



3 2 1



Toshiba's 3.5-inch V300 Video Streaming Hard Drive with up to 3 TB lets you stream, record, edit and play video content on DVR, TV or NVR - with all the efficiency and reliability you need. A 64 MB buffer helps deliver smooth performance, while temperature control technology limits heat buildup, extending service life for added reliability. A drive that's quiet and more efficient than ever, thanks to Toshiba's Silent Seek Technology, and reduced energy consumption.

Use for:

- Video Editing Systems
- Set-Top-Box (STB)
- Digital Video Recorders (DVR)
- · Network Video Recorders (NVR)
- Video Surveillance Systems



3.5" SATA Hard Drive

64 MB buffer

24/7

24/7 operation



Up to 16 cameras



Temperature control

Toshiba Silent Seek Technology


Manual

Installation-and-Safety-Internal-HDDs.pdf 🕹





Product Specifications



Basic Specifications		Box Content	
Form factor	3.5-inch	Box Content	3. H
Interface	6.0 Gbit/s		
Number of cameras supported	16	Physical	
Drive bays supported	up to 8	Weight (approx.)	7(4:
Advanced Format (AF)	Yes	Dimensions	14
RoHS compatible	Yes		
Halogen Free	Yes	Environmental	
Shock Sensor	Yes	Acoustics (idle mode)	2:
			1
Performance		Shock (non-operating)	30
Rotational speed	5940 rpm (3 TB), 5700 rpm (1 TB - 2 TB)	Shock (operating)	7(
Buffer size	64 MB	Vibration (non-operating)	1.
Native Command Queing (NCQ)	supported	Vibration (operating)	0.
Reliability		Temperature (operating / non- operating)	0
Workloads	72TB/year	Power Management	
Unrecoverable error rate	1 per 10E14 bits read		4
24/7 operation	Yes	Consumption - Active Idle	3.
Load / Unload Cycle	300,000		3.
Power Management			
Supply voltage	5VDC (±5%) / 12VDC (±10%)		

Box Content	3.5-inch internal HDD - V300 Video Streaming Hard Drive	
Physical		
Weight (approx.)	700 g max. (2 TB, 3 TB), 450 g max. (1 TB)	
Dimensions	147 (L) x 101.85 (W) x 26.1 (H) mm	
Environmental		
Acoustics (idle mode)	24 dB typ. (3 TB),	
	22 dB typ. (2 TB), 19 dB typ. (1 TB)	
Shock (non-operating)	300 G / 2 ms half sine	
Shock (operating)	70 G / 2 ms duration	
Vibration (non-operating)	1.04 G (2 to 200Hz)	
Vibration (operating)	0.67 G (5 to 500 Hz)	
Temperature (operating / non- operating)	0 to 65° C / -40 to 70°C	
Power Management		
Consumption - Active Idle	4.20 W typ. (3 TB),	
	3.30 W typ. (2 TB), 3.00 W typ. (1 TB)	

Product Range

Part number HDWU130UZSVA (Bulk) HDWU120UZSVA (Bulk) HDWU110UZSVA (Bulk) Capacity 3 TB 2 TB

1 TB

Color

Logistical Information:

Box dimensions n/A Box weight (gross) n/A

Master carton dimensions 321 x 406 x 213 mm

Master carton weight (gross)

16 kg (typ.), 11 kg (typ.) (1TB)

Boxes per master carton 20
Pallet dimensions n/A
Pallet weight (net) n/A
Units per pallet 720

Contact

Toshiba Electronics Europe GmbH

Hansaallee 181 40549 Düsseldorf Germany