## **Key Features**

- · Pre-assembled kit ready for instant use
- Foldable screen with the movable flight case for easy delivery
- · Built-in stand with motorized height adjustment
- Impressive audio from Harman Kardon speakers
- · Seamless large display for rental at any event/exhibition



## Product **Description**

The ViewSonic® LDS135-152 is a foldable 135" All-in-One LED display that boasts instant use, easy delivery, and convenient maintenance, making it an ideal rental-ready solution for events, exhibitions, or any other short-term usage. The pre-assembled design and built-in motorized height adjustment stand enable effortless setup within just a few minutes. Delivery convenience is greatly enhanced with the new foldable screen design, reducing the packaging size of the movable flight case by nearly 50% compared to the previous generation, thus minimizing shipping costs. With the seamless large screen and superior built-in Harman Kardon speakers, be ready to impress your audience everywhere from high-end board rooms and receptions to galleries, auditoriums, and other large venues.



- 1. Harman Kardon Speakers
- 2. Power Button
- 3. HDMI Out
- 4. Audio Out
- 5. S/PDIF Out
- 6. IR In
- 7. USB 2.0 (5V/1.5A) x 2
- 8. LAN & Control
- 9. HDMI 2.0 x 2 10. HDMI 1.4 x 2
- 11. HDMI 2.1
- 12 RS232
- 13. USB-C (5V/2A)
- 14. USB 2.0 (5V/1.5A)
- 15. IR Receiver
- 16. Menu Control: Brightness Level
- 17. Menu Control: Volume
- 18. Menu Control: Input Source
- 19. Power Button
- 20. Indicator Light
- 21. Control Panel: Height Adjustment

22. 360° Silent Wheels

**Visit Us** 

www.viewsonic.com

## **SPECIFICATION**

| SPECIFICATION            |  |
|--------------------------|--|
| Screen Size:             | 135"   |
| Display Area (mm):       | 3000 (H) x 1687.5(V)   |
| Native Resolution:       | 1920x1080  |
| Panel Technology:        | Direct view LED  |
| LED Package Type:        | SMD 3 in 1   |
| Pixel Pitch (mm):        | 1.56   |
| Refresh Rate:            | 4440Hz   |
| Brightness (max.):       | 600 nits (8 levels<br>adjustable)                            |
| Contrast Ratio (typ.):   | 6000:1   |
| Orientation:             | Landscape  |
| Viewing Angles (typ.):   | H = 160, V = 160   |
| LED Lifetime (typ.):     | 100,000 Hours  |
| Local Storage:           | Total 64GB<br>(56GB available storage)                       |
| Embedded OS:             | Android 9.0  |
| Resolution Support:      | VGA(640 x 480) to<br>1080p(1920 x 1080)                      |
| HDTV Compatibility:      | 480i, 480p, 576i, 576p,<br>720p, 1080i, 1080p,<br>2160P/60Hz |
| Horizontal Frequency:    | 23-120 kHz   |
| Vertical Scan Rate:      | 15-135 Hz  |
| INPUT                    |  |
| HDMI:                    | x6<br>(HDMI 2.1 x 1, HDMI 2.0<br>x 3, HDMI 1.4 x 2)          |
| USB Type A:              | x3<br>( USB2.0 x3)   |
| RJ45 Input (Internet):   | x1   |
| IR in:                   | x1   |
| Wi-Fi Input:             | 2.4G/5G Hz   |
| USB Type C:              | x1<br>(Video input、 Power<br>output (5V/2A))                 |
| OUTPUT                   |  |
| HDMI out:                | x2<br>(HDMI 2.0 external<br>x1,internal x1)                  |
| Speaker:                 | 20W x2 (Harman Kardon)                                       |
| Audio out (3.5mm):       | x1   |
| USB Type A (Power):      | Shared with USB input (5V/1.5A x3)                           |
| CONTROL                  |  |
| USB Type A (Services):   | x1(shared with USB A input)                                  |
| RS232 (DB 9-pin female): | x1   |
|                          |  |

**x**1

## **OTHERS**

| OTTERS                             |   |
|------------------------------------|---|
| Power Supply Voltage:              | 100-120V/30A~ 50/60Hz<br>or 220-240V/15A~ 50Hz<br>(vary by country) |
| Power Consumption:                 | 1500W (typ), 2500W<br>(max)<br>< 0.5W (Sleep), < 0W<br>(Off)        |
| Operating Temperature:             | 0~40°C  |
| LED Module Quantity:               | 100   |
| Ingress Protection Rating:         | IP30  |
| Net Weight:                        | 564 lbs<br>(253 kg)   |
| Gross Weight:                      | 998 lbs<br>(453 kg)   |
| Screen Dimensions (WxHxD):         | 1800x1963x770<br>mm(min.)<br>3010x2613x770<br>mm(max.)              |
| Packing Dimensions (WxHxD):        | 74.8x80x31.5 inches<br>(1900x2032x800 mm)                           |
| STANDARD ACCESSORIES               |   |
| Power Cord:                        | x1  |
| LAN Cable (Cat 5A):                | x1 (5m)   |
| Remote Control:                    | x1  |
| QSG:                               | x1  |
| Spare Parts:                       | LED PCB Unit x7   |
| Maintenance Tool:                  | LD-MK-001 x1  |
| OPTIONAL ACCESSORIES               |   |
| Maintenance Tool:                  | LD-MK-001   |
| ViewBoard Cast Button(USB-C):      | VB-WPS-001  |
| ViewBoard Cast Button(USB-A+HDMI): | VB-WPS-003  |
|                                    |   |

 $\label{lem:copyright} \textbf{@ ViewSonic Corporation 2000-2023. All rights reserved.}$ 

IR Receiver: