



360W FOLDABLE SOLAR PANEL

Lightweight, off-grid energy to power your equipment with maximum efficiency. Take your FLEXSOLAR ® 360W foldable solar panel you on your outdoor trips. Conversion efficiency up to 24%, Perfect for outdoor living and unexpected power outages. The solar panel is lightweight, only 32 lbs, foldable, and easy to carry.













FLEXSOLAR is the brand of Flextech Company, a global solar solution manufacturing pioneer. You can rely on the experience and s trength of our product development and innovation. Now, with multiple patents, factory locations and a focus on smart solar solutions, we're proud to introduce our FLEXSOLAR brand. The Power of Light is our vision to provide solar solutions that deliver smart energy f or life





360W FOLDABLE SOLAR PANEL

GENERAL	
Model	F360
Part Number	FLC-E4-323600-1
UPC Number	785249519604
ELECTRICAL SPECIFICATIONS	
Rated Peak Power (Pmax)	360 W
Open Circuit Voltage (Voc)	38.3V
Short Circuit Current (Isc)	12 A
Maximum Power Voltage (Vmp)	31.9 V
Maximum Power Current (Imp)	11.5 A
Module Efficiency	22%
Power Tolerance	±10%
Operating Temperature	-20°C ~ 65°C
Application Level	А
Temperature Coefficient (Pmax)	-0.45%/K
Temperature Coefficient (Voc)	-0.32%/K
Temperature Coefficient (Isc)	+0.02%/K
Standard Test Conditions	1000W/m2, 25°C, AM1.5
MECHANICAL SPECIFICAT	ONS
MECHANICAL SPECIFICAT Solar Cell Type	ONS Monocrystalline
	Monocrystalline 92.7 x 38.3 x 0.1 in-unfold
Solar Cell Type	Monocrystalline 92.7 x 38.3 x 0.1 in-unfold (2355 x 973 x 3.5 mm)
Solar Cell Type	Monocrystalline 92.7 x 38.3 x 0.1 in-unfold (2355 x 973 x 3.5 mm) 38.3 x 24 x 1.6 in-fold
Solar Cell Type	Monocrystalline 92.7 x 38.3 x 0.1 in-unfold (2355 x 973 x 3.5 mm)
Solar Cell Type	Monocrystalline 92.7 x 38.3 x 0.1 in-unfold (2355 x 973 x 3.5 mm) 38.3 x 24 x 1.6 in-fold
Solar Cell Type Dimensions (LxWxD)	Monocrystalline 92.7 x 38.3 x 0.1 in-unfold (2355 x 973 x 3.5 mm) 38.3 x 24 x 1.6 in-fold (973 x 610 x 41 mm) 32 lbs (14.5 kg) with junction
Solar Cell Type Dimensions (LxWxD) Net Product Weight	Monocrystalline92.7 x 38.3 x 0.1 in-unfold (2355 x 973 x 3.5 mm)38.3 x 24 x 1.6 in-fold (973 x 610 x 41 mm)32 lbs (14.5 kg) with junction box and accessoriesGreyIP68 rated in accordance
Solar Cell Type Dimensions (LxWxD) Net Product Weight Backsheet Color	Monocrystalline 92.7 x 38.3 x 0.1 in-unfold (2355 x 973 x 3.5 mm) 38.3 x 24 x 1.6 in-fold (973 x 610 x 41 mm) 32 lbs (14.5 kg) with junction box and accessories Grey
Solar Cell Type Dimensions (LxWxD) Net Product Weight Backsheet Color	Monocrystalline92.7 x 38.3 x 0.1 in-unfold (2355 x 973 x 3.5 mm)38.3 x 24 x 1.6 in-fold (973 x 610 x 41 mm)32 lbs (14.5 kg) with junction box and accessoriesGreyIP68 rated in accordance with UL 3730

PACKAGING & SHIPPING INFORMATION

Retail Box Dimensions (LxWxD) & Weight Quantity 1 unit per retail box: 39.6 x 25.2 x 2.6 in (1005 x 640 x 65mm); 38.1 lbs (17.3 kg)

ACCESSORIES



4-In-1 Solar

Carabiners x 4

Folding bracket x 3

Extension Cable

WARRANTY

12 months limited warranty, register at flexsolarenergy.com

REGULATORY & CERTIFICATION

FCC, CE, RoHS



0.1 in / 3.5 mm





Support: 800-620-1249 support@flexsolarenergy.com flexsolarenergy.com

®ALL rights reserved. ©2013-2024 FLEXSOLAR®is registered in the U.S.