

## MONSOON DOUBLE SIDED OUTDOOR BILLBOARD

A large format banner 'A' frame made from lightweight aluminum, ideal for use with eyelet banners. Monsoon is very easy to use, reusable and is the perfect graphics carrier for venues, events, exhibitions, promotions and indoor or outdoor shows.

# MONSOON

## DOUBLE SIDED OUTDOOR BILLBOARD



We are continually improving and modifying our product range and reserve the right to vary the specifications without prior notice. All dimensions and weights quoted are approximate and we accept no responsibility for variance. E&OE. See Graphic Templates for graphic bleed specifications.

### FEATURES & BENEFITS

- Semi-portable single or double-sided billboard
- Easy grommet graphic attachment
- Includes 6 ground stakes & 24 bungee cords
- 1 inch square aluminum tubes with reinforced plastic mouldings
- Easy push-fit assembly, no tools necessary
- Includes carry bag
- One year hardware warranty against manufacturers defects
- Six months graphic limited warranty

### DIMENSIONS

**Assembled Unit:**  
98.43" w x 37.992" h x 25.197" d

**Frame Size:**  
98.43" w x 39.37" h

### GRAPHICS

**Graphic Material:**  
13 oz Outdoor scrim vinyl

**Total visual area:**  
92.125" w x 32" h

Allow 2" along top and bottom for #3 grommet placement with reinforced edges (plus 1" bleed on top and bottom)

Refer to related graphic template for more information.

### SHIPPING

**Hardware Ships in 1 Box:**

Box 1 (stand): 50" h x 8" w x 8" d / 20 lbs

### ADDITIONAL INFO

Graphic requires 8 grommets with 0.45" (11.5mm) recommended minimum internal diameter. Graphics secured to frame with elastic bungee cords, included.

Approximately 30" between grommets

### Have a Question?

Please contact [support@tradeshowplus.com](mailto:support@tradeshowplus.com)  
Visit: [www.tradeshowplus.com](http://www.tradeshowplus.com)

## ASSEMBLY

### Have a Question?

Please contact [support@tradeshowplus.com](mailto:support@tradeshowplus.com)  
Visit: [www.tradeshowplus.com](http://www.tradeshowplus.com)




1. Open all the end and center 'A' frames



2. Push each locking arm down to secure the frame



3. Push fit the top horizontal tubes into the 'A' frames, ensure the plastic joiners face inwards



4. Push fit the bottom horizontal tubes into the 'A' frames, ensure the plastic joiners face inwards

## GRAPHIC ATTACHMENT



1. Pass the elastic bungee cord through the graphic eyelet



2. Secure elastic bungee around the frame with hook



3. Corner eyelets require a bungee cord loop around the top and side of the frame to properly secure