Set Up Instructions

OneFabric 5ft Straight Tabletop Display

Step 1: Carefully remove frame and graphic from nylon bag.

Step 2: Ensure "adjustable feet" of frame are on the floor. Pull up display into upright position.

Step 3: Lock all hooks between front and back hubs.

Step 4: If supplied with fabric end caps, wrap Velcro fabric edges around all end cap brackets on both sides. Pull past edge if needed to make taut.



WARNING BEFORE COLLAPSING THE FRAME:

Step 1: Both graphic end caps must be detached from end cap brackets before collapsing frame.

Step 2: To avoid damage to the

frame, all hooks must be unhooked and separated from each other.

Once this is done the frame should begin to collapse under its own weight without much effort.




LIGHTS:

(OPTIONAL) Attach lights to top of frame by sliding the plastic "x block" under the rear pole and over the front pole.








Set Up Instructions


OneFabric Graphic Installation

Step 1: Assemble frame and lay flat on its back. Remove existing graphic.

Step 2: Starting at one corner, attach Velcro on the graphic to Velcro on the frame. Note: Velcro on the graphic should extend approx. 1/4" beyond Velcro on the frame (it should not be flush). **Step 3:** Working in a continuous direction around the frame, attach the rest of the graphic. If supplied with end caps, attach end cap Velcro to end cap brackets on both sides.



Step 4: If needed, adjust Velcro for taut fit. Complete.



WARNING BEFORE COLLAPSING THE FRAME:

Step 1: Both graphic end caps must be detached from end cap brackets before collapsing frame.

Step 2: To avoid damage to the

frame, all hooks must be unhooked and separated from each other.

Once this is done the frame should begin to collapse under its own weight without much effort.



