Orbea
10' x 20' Truss System
Dye Sub Printed

TEMPLATE IS @ 1/2 SCALE
Panels OB1 and OB5:
Total Graphic Area: 47"w x 87.75"h
Finished Size: 43"w x 83.75"h
Visual Size: 41"w x 81.75"h

Panels OB2 and OB4:
Total Graphic Area: 29.75"w x 87.75"h
Finished Size: 25.75"w x 83.75"h
Visual Size: 23.75"w x 81.75"h

Panel OB3:
Total Graphic Area: 136.75"w x 87.75"h
Finished Size: 132.75"w x 83.75"h
Visual Size: 132.75"w x 83.75"h

Template requires 1" bleed around the perimeter (2" around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4" w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4"w velcro is applied to the front of the panel)
Notching = 7/8" square that is cut into the appropriate location.
Hinging= 3/4" strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS
OR-G-OB1

BS
OR-G-OB2

FS
OR-G-OB3

panel is notched on all four corners

BS
OR-G-OB4

BS
OR-G-OB5

gray area will be obstructed once finished and mounted

— bleed area
— trim line

Orbea
10’ x 20’ Truss System
Dye Sub Printed



TEMPLATE IS @ 1/2 SCALE
Panels OB1 and OB5:
Total Graphic Area: 47”w x 87.75”h
Finished Size: 43”w x 83.75”h
Visual Size: 41”w x 81.75”h

Panels OB2 and OB4:
Total Graphic Area: 29.75”w x 87.75”h
Finished Size: 25.75”w x 83.75”h
Visual Size: 23.75”w x 81.75”h

Panel OB3:
Total Graphic Area: 136.75”w x 87.75”h
Finished Size: 132.75”w x 83.75”h
Visual Size: 132.75”w x 83.75”h

Template requires 1” bleed around the perimeter (2” around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4” w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4”w velcro is applied to the front of the panel)
Notching = 7/8” square that is cut into the appropriate location.
Hinging= 3/4” strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

– CMYK Color Mode
– All Solid Coated Pantone colors should be called out in the art as spot colors
– Embed all images and support files
– Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
– All fonts must be created to outlines
– Do not scale artboard
– Background color/images must bleed to the edge of artboard
– Do not use spot colors from template in your artwork as they will not print

BS

OR-G-OB1

bleed area
trim line

BS

OR-G-OB2

FS

OR-G-OB3

panel is notched
on all four
corners

BS

OR-G-OB4

BS

OR-G-OB5

gray area will
be obstructed
once finished
and mounted