Phoenix
10' x 20' Truss System
Dye Sub Printed

TEMPLATE IS @ 1/2 SCALE
Panels PX1, PX2, PX6 and PX7:
Total Graphic Area: 42.125"w x 87.75"h
Finished Size: 38.125"w x 83.75"h

Panel PX3 and PX5:
Total Graphic Area: 47"w x 87.75"h
Finished Size: 43"w x 83.75"h

Panel PX4:
Total Graphic Area: 29.75"w x 87.75"h
Finished Size: 25.75"w x 83.75"h

Template requires 1" bleed around the perimeter (2" around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4" w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4"w velcro is applied to the front of the panel)
Notching = 7/8" square that is cut into the appropriate location.
Hinging= 3/4" strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS
OR-G-PX1

bleed area
trim line

BS
OR-G-PX2

BS
OR-G-PX3

panel is notched
on top and bottom right
side and inward
hinged on right side

BS
OR-G-PX4

panel is notched
on all 4 corners
and inward hinged
on left side

BS
OR-G-PX5

panel is notched
on top and bottom left
side and inward
hinged on left side

BS
OR-G-PX6

BS
OR-G-PX7

gray area will
be obstructed
once finished
and mounted

Phoenix
10’ x 20’ Truss System
Dye Sub Printed



TEMPLATE IS @ 1/2 SCALE
Panels PX1, PX2, PX6 and PX7:
Total Graphic Area: 42.125”w x 87.75”h
Finished Size: 38.125“w x 83.75”h

Panel PX3 and PX5:
Total Graphic Area: 47”w x 87.75”h
Finished Size: 43“w x 83.75”h

Panel PX4:
Total Graphic Area: 29.75”w x 87.75”h
Finished Size: 25.75“w x 83.75”h

Template requires 1” bleed around the perimeter (2” around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4“ w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4“w velcro is applied to the front of the panel)
Notching = 7/8” square that is cut into the appropriate location.
Hinging= 3/4” strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

– CMYK Color Mode
– All Solid Coated Pantone colors should be called out in the art as spot colors
– Embed all images and support files
– Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
– All fonts must be created to outlines
– Do not scale artboard
– Background color/images must bleed to the edge of artboard
– Do not use spot colors from template in your artwork as they will not print

BS

OR-G-PX1

— bleed area
— trim line

BS

OR-G-PX2

BS

OR-G-PX3

panel is notched
on top and bottom right
side and inward
hinged on right side

BS

OR-G-PX4

panel is notched
on all 4 corners
and inward hinged
on left side

BS

OR-G-PX5

panel is notched
on top and bottom left
side and inward
hinged on left side

BS

OR-G-PX6

BS

OR-G-PX7

gray area will
be obstructed
once finished
and mounted