



## PRODUCT NAME – RUST-X RP oil

**PRODUCT CODE – VCI 120 A EX MIL- PRF- 32033**

## TECHNICAL DATASHEET

### PRODUCT DESCRIPTION

RUSTX oils contain VCI chemicals, which work in contact phase as well as in the vapor phase and protect components by its dual action.

RUSTX–120 A is a low viscosity grade of rust preventive oil having excellent thixotropic properties and holds well on surfaces that may be super finished or vertically placed.

The product can be used for protection of Cold Rolled Steel, Engine Components, as well as large equipment where indoor open storages are required.

The VCI action of the oil makes it suitable for spraying within hollow equipment such as boilers, heat exchangers, reactors, storage tanks, pipes etc. The VCI fraction evaporates and reaches hard to reach surfaces where the direct oil spray cannot reach and protects the equipment from corrosion.

All RUST-X rust preventive oils are Barium & Heavy Metal Free.

### FEATURES

- VCI Properties
- Very light lubricating film
- Thixotropic properties
- Long Term Corrosion Prevention
- Electrostatically sprayable
- Allow 2-10 minutes drain and drying time depending upon product requirement
- Easily washable with water and solvent based products
- Excellent protection against acidic and saline environments
- Paintable in paint line
- Non Sticky soft film
- Found to be equivalent to MIL PRF 32033

### APPLICATIONS

- Machined Steel Components
- Castings
- Forgings
- CR sheets
- Bearings, Gears
- Transmission Components
- Axles, Process Equipment
- Flanges
- Valves etc.



**PRODUCT NAME – RUST-X RP oil**

**PRODUCT CODE – VCI 120 A EX MIL- PRF- 32033**

## TECHNICAL DATASHEET

### TECHNICAL SPECIFICATION

### APPLICATION PICTURES



Physical Properties	Test Method	Value
Color	Visual	Amber Clear
Viscosity @ cSt @ 40°C	ASTM D 445	12-18 cSt
Specific Gravity 60°F	ASTM D 1298	0.889
Flash Point	ASTM D 92	170 °C
Volatiles by % (by weight)		1 %
Coverage (sq m/ Lt)		100
Film thickness	IS 2074	2-4 Microns
Pour Point	ASTM D 97	-6°C
Saponification Value (mg KOH/gm)	ASTM D 94	<7.0
Salt Spray Protection	ASTM B 117	< 96 hours
Salt Spray in VCI Packaging	ASTM B 117	720 hours +
Removability Test		Pass
Humidity Chamber	ASTM D 1748	720 hours +
Indoor Protection Life (open)		2 months
Indoor protection life (packed)		2 years
Packaged Protection Life (In VCI Packaging)		Up to 5 Years

### PACKAGING AND STORAGE

Store in a cool dry place and always keep RPO sealed when not in use.

USA - 14310 Gannet St , La Mirada, California  
 info@rustxusa.com    www.rustxusa.com  
 Italy | France | India | China | Mexico





## PRODUCT NAME – RUST-X RP oil

**PRODUCT CODE – VCI 120 A EX MIL- PRF- 32033**

## TECHNICAL DATASHEET

### USAGE

Dipping by far is the best method for establishing an even layer on the component. Other methods may be used such as mist spraying, electrostatic spraying, brushing, automatic conveyor spray or dip process spray. It is important that the complete surface of the component is coated with the rust preventive oil.

Use of gloves while handling the components as well as immediate packaging is important. In case the components carry cutting oils or water from previous processes, dewatering with CL005 is recommended

### DISPOSAL

Recommendation: Do not allow product to reach sewage system.

Disposal of product or waste must comply with official local regulations.

Packaging that cannot be recycled must be disposed in the same manner as the product.

### HEAVY METALS DECLARATION

RUST-X Rust Preventive products do not contain Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent Chromium (Cr6), Polybrominated biphenyls (PBB), or Polybrominated di-phenylether complying with the restricted substances listed in Article 4(1) of the RoHS Directive. RUST-X Rust Preventive Oils are also REACH

Compliant for exports to the European Union.

### SAFETY INFORMATION

- Keep Out Of Reach Of Children
- Keep Container Tightly Closed
- Not For Internal Consumption
- Consult Material Safety Data Sheet For More Information
- Safe for people
- This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom and CA WHMIS regulations.
- Rust-X VCI chemistry is safe for sensitive electronics.
- Rust-X VCI chemistry imposes No galvanic effects, residues or changes in the properties of metals. The protective molecules dissipate upon opening of package.

### DECLARATION

This Data sheet and information it contains is considered to be accurate at the date of printing. No representation or warranty, expressed or implied is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations.



## PRODUCT NAME – RUST-X RP oil

PRODUCT CODE – VCI 120 A EX MIL- PRF- 32033

### TECHNICAL DATASHEET

#### LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on validations and tests conducted by HI TECH INTERNATIONAL/RUST-X or its partners and are believed to be reliable, but the accuracy or completeness thereof is not guaranteed. We warrant our products will be free from defects when shipped to customer. Our obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Rust-X, Hi Tech International or its partners or agent of the claimed defect within 3 months after shipment of product to customer. Customer shall pay all freight charges for replacement products. We shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. And any financial claims shall be limited to the value of the film sold.

Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of the company. The foregoing warranty is exclusive and in lieu of all other warranties, express, implied or statutory, including without limitation any implied warranty of merchantability or of fitness for a particular purpose. In

no case shall HI TECH INTERNATIONAL/RUST-X be liable for incidental or consequential damages.

#### GLOBAL SUPPORT

Algeria Angola Argentina Australia Austria Bangladesh Belarus Belgium Bhutan Bolivia Brazil Canada Chile China Colombia Czech Republic Democratic Republic of the Congo Denmark Ecuador Estonia Finland France Gabon Germany Hungary India Indonesia Ireland Italy Japan Kazakhstan Korea Latvia Lithuania Luxembourg Malaysia Mexico Monaco Morocco Nepal Netherlands Nigeria Norway Peru Philippines Poland Portugal Republic of Congo Romania Russia Singapore Slovak Republic Slovenia South Africa Spain Sri Lanka Sweden Switzerland Taiwan Thailand Tunisia Turkey Ukraine United Arab Emirates and MENA (Middle East & North Africa) United Kingdom United States Uruguay Vietnam

DISTRIBUTED BY -

FOR INDUSTRIAL USE ONLY

Revision No. 1 Revision Date: April 2019

