PRODUCT SPECIFICATIONS

7008B

Tradesman® Plus 1D Standard Non-belted Full Body Harness, Tongue Buckle Leg Adjustment

Features :

- Features integral tri-layer padded shoulder yoke to provide breathable user comfort
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment
- Dorsal D-ring, quick connect chest, and tongue buckle leg closures are all durably plated alloy steel
- Quick-connect buckle features visual indicators showing positive connection
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Complies with ANSI Z359.11-2014



Material Specifications					
Webbing	Polyester; 5,000 lb min. static strength				
D-ring	Plated alloy steel; 5,000 lb min. static strength				
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength				

Performance S	pecifications
Static Strength	3,600 lb min.
ANSI User	130 to 310 lb
Capacity	max.
OSHA User	130 to 425 lb
Capacity	max.

Co	ompliant With:
OSHA	1926.502 and 1910.66
CSA	Z259.10-2018
ANSI	Z359.11-2014

Sizes & Part Numbers						
7008BXS - XS *	7008BSM - Dual-size Small/Med	7008BLX - Dual-size Large/XL	7008B2X - 2X	7008B3X - 3X *	*Sizes that meet CSA Z259.10- 2018 standard	

