

7021BFD

Journeyman Flex® Aluminum 2D Climbing Non-belted Full Body Harness

Features :

- Features integral padded shoulder yoke and hip-to-seat leg pads to provide advanced breathable user comfort
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit
- Features lightweight forged aluminum alloy dorsal D-ring and steel sternal D-ring
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Quick-connect chest buckle features visual indicator showing positive connection
- Includes fully adjustable suspension trauma relief system
- Meets OSHA 1926.502 and 1910.66 Regulations



TRAUMA RELIEF PACK NOW INCLUDED

Material Specifications		Performance Specifications		Compliant With:	
Webbing	Polyester; 5,000 lb min. static strength	Static Strength	3,600 lb min.	CSA	Z259.10-2018
D-rings	Aluminum Alloy and Plated Alloy Steel; 5,000 lb min. static strength	ANSI User Capacity	130 to 310 lb max.	OSHA	1926.502 and 1910.66
Buckles and Adjusters	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength	OSHA User Capacity	130 to 425 lb max.		

Sizes & Part Numbers					
7021BFDS - Small	7021BFDM - Medium	7021BFDL - Large	7021BFDXL - XL	7021BFD2X - 2X	7021BFD3X - 3X

