PRODUCT SPECIFICATIONS

FALLTECH®

CONTACT SALES

7021FD

Journeyman Flex® Steel 2D Climbing Non-belted Full Body Harness

Features:

- Features integral padded shoulder yoke and hip-toseat leg pads to provide advanced breathable user comfort
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment
- Dorsal and sternal D-rings, mating buckle chest, and tongue buckle leg closures are all durably plated alloy steel
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Includes fully adjustable suspension trauma relief system
- Complies with ANSI Z359.11-2014



Material Specifications						
Webbing	Polyester; 5,000 lb min. static strength					
D-rings	Plated alloy steel; 5,000 lb min. static strength					
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength					

Performance S	pecifications		
Static Strength	3,600 lb min.		
ANSI User	130 to 310 lb		
Capacity	max.		
OSHA User	130 to 425 lb		
Capacity	max.		

Co	ompliant With:
CSA	Z259.10-2018
OSHA	1926.502 and 1910.66
ANSI	Z359.11-2014

Sizes & Part Numbers					pers
7021FDS -	7021FDM -	7021FDL -	7021FDXL -	7021FD2X -	7021FD3X -
Small	Medium	Large	XL	2X	3X

