

## 7027B

### Journeyman Flex® Aluminum 3D Retrieval Non-belted Full Body Harness

#### Features :

- Features integral padded shoulder yoke and hip-to-seat leg pads to provide advanced breathable user comfort
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit
- Features lightweight forged aluminum alloy dorsal D-ring and steel shoulder D-rings
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Quick-connect chest buckle features visual indicator showing positive connection
- Includes fully adjustable suspension trauma relief system
- Complies with ANSI Z359.11-2014



TRAUMA RELIEF PACK NOW INCLUDED

| Material Specifications      |  |
|------------------------------|--|
| <b>Webbing</b>               | Polyester; 5,000 lb min. static strength                             |
| <b>D-rings</b>               | Aluminum Alloy and Plated Alloy Steel; 5,000 lb min. static strength |
| <b>Buckles and Adjusters</b> | Aluminum alloy and plated alloy steel; 3,372 lb min. static strength |

| Performance Specifications |                    |
|----------------------------|--------------------|
| <b>Static Strength</b>     | 3,600 lb min.      |
| <b>ANSI User Capacity</b>  | 130 to 310 lb max. |
| <b>OSHA User Capacity</b>  | 130 to 425 lb max. |

| Compliant With: |                      |
|-----------------|----------------------|
| <b>CSA</b>      | Z259.10-2018         |
| <b>ANSI</b>     | Z359.11-2014         |
| <b>OSHA</b>     | 1926.502 and 1910.66 |

| Sizes & Part Numbers     |              |  |
|--------------------------|--------------|--|
| 7027B - UniFit (S, M, L) | 7027BXL - XL |  |

