# **PRODUCT SPECIFICATIONS**

# FALLTECH®

**CONTACT SALES** 

## 7035QC

### Journeyman Flex® Steel 3D Construction Belted Full Body Harness

#### Features:

- Features integral padded shoulder yoke, hip-to-seat leg, and 6" waist support positioning pads to provide advanced breathable user comfort
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment
- Dorsal and hip D-rings and quick connect chest and leg buckles are all durably plated alloy steel
- Quick-connect buckles feature visual indicators showing positive connection
- Includes fully adjustable suspension trauma relief system
- Complies with ANSI Z359.11-2014



Material Specifications					
Webbing	Polyester; 5,000 lb min. static strength				
D-rings	Plated alloy steel; 5,000 lb min. static strength				
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength				

Performance Specifications						
Static Strength	3,600 lb min.					
ANSI User	130 to 310 lb					
Capacity	max.					
OSHA User	130 to 425 lb					
Capacity	max.					

Compliant With:					
CSA	Z259.10-2018				
ANSI	Z359.11-2014				
OSHA	1926.502 and 1910.66				

Sizes & Part Numbers						
7035QCS - Small	7035QCM - Medium	7035QCL - Large	7035QCXL - XL	7035QC2X - 2X	7035QC3X4X - Dual-size 3X/4X	