PRODUCT SPECIFICATIONS

FALLTECH®

CONTACT SALES

7082B3D

Advanced ComforTech® Gel 3D Standard Non-belted Harness

Features:

- Shoulder yoke and sub-pelvic leg pads feature exclusive gel endoskeleton for unsurpassed user
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit
- Features lightweight forged aluminum alloy dorsal and hip D-rings
- Quick-connect chest and leg buckles feature visual indicators showing positive connection
- Includes fully adjustable suspension trauma relief system
- Complies with ANSI Z359.11-2014



Material Specifications		
Webbing	Polyester; 5,000 lb min. static strength	
D-rings	Aluminum alloy; 5,000 lb min. static strength	
Buckles and Adjusters	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength	

Performance Specifications				
Static Strength	3,600 lb min.			
ANSI User	130 to 310 lb			
Capacity	max.			
OSHA User	130 to 425 lb			
Capacity	max.			

Compliant With:			
OSHA	1926.502 and 1910.66		
CSA	Z59.10-2018		
ANSI	Z359.11-2014		
	·		

Sizes & Part Numbers				
7082B3DS -	7082B3DM -	7082B3DL -	7082B3DXL -	
Small	Medium	Large	XL	