PRODUCT SPECIFICATIONS

FALLTECH®

CONTACT SALES

7082B

Advanced ComforTech® Gel 1D Standard Non-belted Full Body Harness

Features:

- Shoulder yoke and sub-pelvic leg pads feature exclusive gel endoskeleton for unsurpassed user comfort
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit
- Features lightweight forged aluminum alloy dorsal Dring
- Quick-connect chest and leg buckles feature visual indicators showing positive connection
- Includes fully adjustable suspension trauma relief system
- Complies with ANSI Z359.11-2014



| Material Specifications | | | | | |
|--------------------------|--|--|--|--|--|
| Webbing | Polyester; 5,000 lb min. static strength | | | | |
| D-ring | Aluminum alloy; 5,000 lb min. static strength | | | | |
| Buckles and Adjusters | Aluminum alloy and plated alloy steel; 3,372 lb min. static strength | | | | |

| Performance S | pecifications |
|-----------------|---------------|
| Static Strength | 3,600 lb min. |
| ANSI User | 130 to 310 lb |
| Capacity | max. |
| OSHA User | 130 to 425 lb |
| Capacity | max. |

| Compliant With: | | | | | |
|-----------------|----------------------|--|--|--|--|
| CSA | Z59.10-2018 | | | | |
| OSHA | 1926.502 and 1910.66 | | | | |
| ANSI | Z359.11-2014 | | | | |

| Sizes & Part Numbers | | | | | |
|----------------------|--------------------|-------------------|--------------|--------------|--------------|
| 7082BS - Small | 7082BM - Medium | 7082BL - Large | 7082BXL - XL | 7082B2X - 2X | 7082B3X - 3X |