## **PRODUCT SPECIFICATIONS**



**CONTACT SALES** 

## **7088BFD**

## FlowTech LTE® 4D Construction Climbing Full Body Harness, Tongue Buckle Leg Adjustment

## Features:

- Lightweight Flowscape® shoulder yoke, sub-pelvic leg, and 7" waist support positioning pads deliver evaporative breathability
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit
- Features lightweight forged aluminum alloy dorsa, hip, and sternal D-rings
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Quick-connect chest buckle features visual indicator showing positive connection
- Waist support pad features paired tool tether connection rings for tools weighing up to 5 lb
- Meets OSHA 1926.502 and 1910.66 Regulations



Material Specifications		
Webbing	Polyester; 5,000 lb min. static strength	
D-rings	Aluminum alloy; 5,000 lb min. static strength	
Buckles and Adjusters	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength	

Performance Specifications				
Static Strength	3,600 lb min.			
ANSI User	130 to 310 lb			
Capacity	max.			
OSHA User	130 to 425 lb			
Capacity	max.			

Compliant With:			
OSHA	1926.502 and 1910.66		

Sizes & Part Numbers				
7088BFDS -	7088BFDM -	7088BFDL -	7088BFDXL -	
Small	Medium	Large	XL	

