PRODUCT SPECIFICATIONS



CONTACT SALES

7088B

FlowTech LTE® 3D Construction Belted Full Body Harness, Tongue Buckle Leg Adjustment

Features:

- Lightweight Flowscape® shoulder yoke, sub-pelvic leg, and 7" waist support positioning pads deliver evaporative breathability
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit
- Features lightweight forged aluminum alloy dorsal and hip D-rings
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Quick-connect chest buckle features visual indicator showing positive connection
- Waist support pad features paired tool tether connection rings for tools weighing up to 5 lb
- Complies with ANSI Z359.11-2014



Mater	ial Specifications
Webbing	Polyester; 5,000 lb min. static strength
D-rings	Aluminum alloy; 5,000 lb min. static strength
Buckles and Adjusters	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength

Performance S	pecifications		
Static Strength	3,600 lb min.		
ANSI User	130 to 310 lb		
Capacity	max.		
OSHA User	130 to 425 lb		
Capacity	max.		

Compliant With:				
OSHA	1926.502 and 1910.66			
ANSI	Z359.11-2014			

Sizes & Part Numbers					
7088BS - Small	7088BM - Medium	7088BL - Large	7088BXL - XL	7088B2X - 2X	7088B3X - 3X