

**7089BQ**

**FlowTech LTE® 3D Construction Belted Full Body Harness, Locking Quick Connect Adjustment**

**Features :**

- Lightweight Flowscape® shoulder yoke, sub-pelvic leg, and 7" waist support positioning pads deliver evaporative breathability
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit
- Features lightweight forged aluminum alloy dorsal and hip D-rings
- Also features exclusive locking quick-connect leg buckles for added protection against accidental disengagement
- Quick-connect chest buckle features visual indicator showing positive connection
- Waist support pad features paired tool tether connection rings for tools weighing up to 5 lb
- Complies with ANSI Z359.11-2014



Material Specifications	
<b>Webbing</b>	Polyester; 5,000 lb min. static strength
<b>D-rings</b>	Aluminum alloy; 5,000 lb min. static strength
<b>Buckles and Adjusters</b>	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength

Performance Specifications	
<b>Static Strength</b>	3,600 lb min.
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 425 lb max.

Compliant With:	
<b>OSHA</b>	1926.502 and 1910.66
<b>ANSI</b>	Z359.11-2014

Sizes & Part Numbers				
7089BQS - Small	7089BQM - Medium	7089BQL - Large	7089BQXL - XL	

