

7089B

FlowTech LTE® 3D Construction Belted Full Body Harness

Features :

- Lightweight Flowscape® shoulder yoke, sub-pelvic leg, and 7" waist support positioning pads deliver evaporative breathability
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit
- Features lightweight forged aluminum alloy dorsal and hip D-rings
- Quick-connect chest and leg buckles feature visual indicators showing positive connection
- Waist support pad features paired tool tether connection rings for tools weighing up to 5 lb
- Complies with ANSI Z359.11-2014



Material Specifications	
Webbing	Polyester; 5,000 lb min. static strength
D-rings	Aluminum alloy; 5,000 lb min. static strength
Buckles and Adjusters	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
OSHA	1926.502 and 1910.66
ANSI	Z359.11-2014

Sizes & Part Numbers					
7089BS - Small	7089BM - Medium	7089BL - Large	7089BXL - XL	7089B2X - 2X	7089B3X - 3X

