

8123BQC

FT-One™ 3D Construction Belted Full Body Harness, Quick Connect Adjustments

Features :

- Comfort Legs™ lateral leg strap construction greatly improves mobility and comfort
- New Modular Belt System™ allows for custom configuration of tool bag and pouch positions for ease of use, comfort, and efficiency
- ArrowGrip™ dorsal D-ring plate and new slip-resistant connectors minimize slippage for maximum comfort and minimal adjustment throughout the day
- Waist belt features four ANSI/ISEA 121-compliant tool tether anchor attachments, rated at five pounds each
- Industry-exclusive shoulder pad material is abrasion resistant to mitigate excess wear and keep the harness in service longer
- Advanced gel padding material disperses harness loads, eliminating hot spots and pressure points for all-day comfort
- Durable lanyard keeper design improves versatility and reusability while maintaining ANSI compliance
- Includes fully adjustable suspension trauma relief system
- Quick-connect buckles feature visual indicator showing positive connection
- FT-One™ Patent Pending



Material Specifications	
Webbing	Polyester; 5,000 lb min. static strength
D-rings	Aluminum Alloy; 5,000 lb min. static strength
Buckles and Adjusters	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
ANSI	Z359.11-2014
OSHA	1926.502 and 1910.66

Sizes & Part Numbers						
8123BQCXS - XS	8123BQCS - Small	8123BQCM - Medium	8123BQCL - Large	8123BQCXL - XL	8123BQC2X - 2X	8123BQC3X - 3X