

# 8124B3DQC

FT-One™ 3D Standard Non-Belted Full Body Harness, Quick Connect Adjustments

**Features :**

- Comfort Legs™ lateral leg strap construction greatly improves mobility and comfort
- ArrowGrip™ dorsal D-ring plate and new slip-resistant connectors minimize slippage for maximum comfort and minimal adjustment throughout the day
- Industry-exclusive shoulder pad material is abrasion resistant to mitigate excess wear and keep the harness in service longer
- Advanced gel padding material disperses harness loads, eliminating hot spots and pressure points for all-day comfort
- Durable lanyard keeper design improves versatility and reusability while maintaining ANSI compliance
- Includes fully adjustable suspension trauma relief system
- Quick-connect buckles feature visual indicator showing positive connection
- FT-One™ Patent Pending
- Complies with ANSI Z359.11-2014



Material Specifications	
<b>Webbing</b>	Polyester; 5,000 lb min. static strength
<b>D-rings</b>	Aluminum Alloy; 5,000 lb min. static strength
<b>Buckles and Adjusters</b>	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength

Performance Specifications	
<b>Static Strength</b>	3,600 lb min.
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 425 lb max.

Compliant With:	
<b>ANSI</b>	Z359.11-2014
<b>OSHA</b>	1926.502 and 1910.66

Sizes & Part Numbers						
8124B3DQCXS - XS	8124B3DQCS - Small	8124B3DQCM - Medium	8124B3DQCL - Large	8124B3DQCXL - XL	8124B3DQC2X - 2X	8124B3DQC3X - 3X