

8124BQC

FT-One™ 1D Standard Non-Belted Full Body Harness, Quick Connect Adjustments

Features :

- Comfort Legs™ lateral leg strap construction greatly improves mobility and comfort
- ArrowGrip™ dorsal D-ring plate and new slip-resistant connectors minimize slippage for maximum comfort and minimal adjustment throughout the day
- Industry-exclusive shoulder pad material is abrasion resistant to mitigate excess wear and keep the harness in service longer
- Advanced gel padding material disperses harness loads, eliminating hot spots and pressure points for all-day comfort
- Durable lanyard keeper design improves versatility and reusability while maintaining ANSI compliance
- Includes fully adjustable suspension trauma relief system
- Quick-connect buckles feature visual indicator showing positive connection
- FT-One™ Patent Pending
- Complies with ANSI Z359.11-2014



| Material Specifications | |
|------------------------------|--|
| Webbing | Polyester; 5,000 lb min. static strength |
| D-rings | Aluminum Alloy; 5,000 lb min. static strength |
| Buckles and Adjusters | Aluminum alloy and plated alloy steel; 3,372 lb min. static strength |

| Performance Specifications | |
|----------------------------|--------------------|
| Static Strength | 3,600 lb min. |
| ANSI User Capacity | 130 to 310 lb max. |
| OSHA User Capacity | 130 to 425 lb max. |

| Compliant With: | |
|-----------------|----------------------|
| ANSI | Z359.11-2014 |
| OSHA | 1926.502 and 1910.66 |

| Sizes & Part Numbers | | | | | | |
|----------------------|------------------|-------------------|------------------|----------------|----------------|----------------|
| 8124BQCXS - XS | 8124BQCS - Small | 8124BQCM - Medium | 8124BQCL - Large | 8124BQCXL - XL | 8124BQC2X - 2X | 8124BQC3X - 3X |