FALLTECH®

8127B

FT-One[™] 3D Construction Belted Full Body Harness, Tongue Buckle Leg Adjustments

Features :

- Comfort Legs[™] lateral leg strap construction greatly improves mobility and comfort
- New Modular Belt System[™] allows for custom configuration of tool bag and pouch positions for ease of use, comfort, and efficiency
- ArrowGrip[™] dorsal D-ring plate and new slipresistant connectors minimize slippage for maximum comfort and minimal adjustment throughout the day
- Waist belt features four ANSI/ISEA 121-compliant tool tether anchor attachments, rated at five pounds each
- Industry-exclusive shoulder pad material is abrasion resistant to mitigate excess wear and keep the harness in service longer
- Advanced gel padding material disperses harness loads, eliminating hot spots and pressure points for all-day comfort
- Durable lanyard keeper design improves versatility and reusability while maintaining ANSI compliance
- Includes fully adjustable suspension trauma relief system
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit



• FT-One[™] Patent Pending

Material Specifications Polyester: 5,000 lb min.			
Webbing	Polyester; 5,000 lb min. static strength	Sta	
D-rings	Aluminum Alloy; 5,000 lb min. static strength	ANS Cap	
	min. static strength		
Buckles and Adjusters	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength	Сар	

Performance Specifications						
Static Strength	3,600 lb min.					
ANSI User	130 to 310 lb					
Capacity	max.					
OSHA User	130 to 425 lb					
Capacity	max.					

Compliant With:					
ANSI	Z359.11-2014				
OSHA	1926.502 and 1910.66				

Sizes & Part Numbers									
8127BXS - XS	8127BS - Small	8127BM - Medium	8127BL - Large	8127BXL - XL	8127B2X - 2X	8127B3X - 3X			