

8128B3D

FT-One™ 3D Standard Non-Belted Full Body Harness, Tongue Buckle Leg Adjustments

Features:

- Comfort Legs™ lateral leg strap construction greatly improves mobility and comfort
- ArrowGrip™ dorsal D-ring plate and new slipresistant connectors minimize slippage for maximum comfort and minimal adjustment throughout the day
- Industry-exclusive shoulder pad material is abrasion resistant to mitigate excess wear and keep the harness in service longer
- Advanced gel padding material disperses harness loads, eliminating hot spots and pressure points for all-day comfort
- Durable lanyard keeper design improves versatility and reusability while maintaining ANSI compliance
- Includes fully adjustable suspension trauma relief system
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- FT-One[™] Patent Pending
- Complies with ANSI Z359.11-2014



Material Specifications				
Webbing	Polyester; 5,000 lb min. static strength			
D-rings	Aluminum Alloy; 5,000 lb min. static strength			
Buckles and Adjusters	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength			

Performance Specifications							
Static Strength	3,600 lb min.						
ANSI User	130 to 310 lb						
Capacity	max.						
OSHA User	130 to 425 lb						
Capacity	max.						

Co	empliant With:
ANSI	Z359.11-2014
OSHA	1926.502 and 1910.66

Sizes & Part Numbers						
8128B3DXS -	8128B3DS -	8128B3DM -	8128B3DL -	8128B3DXL -	8128B3D2X -	8128B3D3X -
XS	Small	Medium	Large	XL	2X	3X