

## 6814150K

### Rescue and Descent Worksite Kit with Storage Bag

#### Features :

- 7/16" sheathed-core kernmantle rope lifeline resists moisture and abrasion for longer life
- Integral triple-mode lifting capability includes handwheel, ratcheting handle and power drill adapter.
- Telescoping Ratchet lifting handle adjusts from 12" to 18" for unmatched rescue lifting leverage
- Bi-directional design provides shuttle operation for multiple successive descending users
- Rope lifeline features aluminum alloy connectors for lighter weight
- Device features integral belay hooks and swiveling aluminum attachment carabiner
- Also includes 6' pass-through choker anchor and 28" backpack-style storage bag
- Complies with ANSI Z359.4-2013



Material Specifications	
<b>Rope</b>	7/16" kernmantle polyamide blend
<b>Connectors</b>	Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength
<b>Housing</b>	Powder coated aluminum

Performance Specifications	
<b>Max Descent Height</b>	524' for 2 users
<b>Max Descent Load</b>	440 lb for 2 users
<b>Descent Speed</b>	2.6' per second for 1 user
<b>Cumulative Descent Distance</b>	25,200' or 48 descents with 220 lb
<b>Cumulative Descent Distance</b>	2,620' or 5 descents with 440 lb
<b>Max Lifting Height</b>	524' at 440 lb
<b>Max Work Lifting Load</b>	308 lb

Compliant With:	
<b>ANSI</b>	Z359.4-2013

Sizes & Part Numbers				
681450K - 50'	6814150K - 150'	6814300K - 300'	6814500K - 500'	

## 68030TC

### Adjustable-reach Carbon Fiber Rescue Pole with Carabiner

#### Features :

- Telescoping adjustment extends user's reach from 4' to 17'
- Carbon fiber pole material significantly reduces bending when extended for easier use during rescue operations
- Features six length-securing twist-locks for maintaining selected adjustments
- Includes aluminum alloy carabiner, storage bag and machined aluminum capture clip



#### Material Specifications

Rescue Pole	Carbon Fiber
Connector	Aluminum Alloy; 5,000 lb min. static strength with 3,600 lb gate strength

#### Compliant With: