

7009B

Tradesman® Plus 3D Standard Non-belted Full Body Harness

Features :

- Features integral tri-layer padded shoulder yoke to provide breathable user comfort
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment
- Dorsal and hip D-rings, quick connect chest, and mating buckle leg closures are all durably plated alloy steel
- Quick-connect buckle features visual indicators showing positive connection
- Complies with ANSI Z359.11-2014



Material Specifications	
Webbing	Polyester; 5,000 lb min. static strength
D-rings	Plated alloy steel; 5,000 lb min. static strength
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
CSA	Z259.10-2018
ANSI	Z359.11-2014
OSHA	1926.502 and 1910.66

Sizes & Part Numbers						
7009BXS - XS	7009BSM - Dual-size Small/Med	7009BLX - Dual-size Large/XL	7009BX/2X- Dual-size XL/2X *	7009B2X - 2X	7009B3X - 3X	*Sizes that meet CSA Z259.10-2018 standard

