PRODUCT SPECIFICATIONS

FALLTECH®

CONTACT SALES

7021QC

Journeyman Flex® Steel 1D Standard Non-belted Full Body Harness

Features:

- Features integral padded shoulder yoke and hip-toseat leg pads to provide advanced breathable user comfort
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment
- Dorsal D-ring and quick connect chest and leg buckles are all durably plated alloy steel
- Quick-connect buckles feature visual indicators showing positive connection
- Includes fully adjustable suspension trauma relief system
- Complies with ANSI Z359.11-2014



Material Specifications		
Webbing	Polyester; 5,000 lb min. static strength	
D-ring	Plated alloy steel; 5,000 lb min. static strength	
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength	

Performance Specifications			
Static Strength	3,600 lb min.		
ANSI User	130 to 310 lb		
Capacity	max.		
OSHA User	130 to 425 lb		
Capacity	max.		

Compliant With:		
CSA	Z259.10-2018	
ANSI	Z359.11-2014	
OSHA	1926.502 and 1910.66	
·		

Sizes & Part Numbers			
7021QC - UniFit (S, M, L)	7021QCXL - XL	7021QC2X3X - Dual-size 2X/3X	