PRODUCT SPECIFICATIONS

FALLTECH®

CONTACT SALES

7028

Journeyman Flex® Steel 2D Cross-over Climbing Full Body Harness

Features:

- Features integral vented and padded dorsal keeper to provide advanced breathable user comfort
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment
- Dorsal and sternal D-rings, mating buckle chest, and tongue buckle leg closures are all durably plated alloy steel
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Includes fully adjustable suspension trauma relief system
- Complies with ANSI Z359.11-2014



Material Specifications		
Webbing	Polyester; 5,000 lb min. static strength	
D-rings	Plated alloy steel; 5,000 lb min. static strength	
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength	

Performance Specifications		
Static Strength	3,600 lb min.	
ANSI User	130 to 310 lb	
Capacity	max.	
OSHA User	130 to 425 lb	
Capacity	max.	

Compliant With:		
OSHA	1926.502 and 1910.66	
CSA	Z259.10-2018	
ANSI	Z359.11-2014	

Sizes & Part Numbers		
7028 - UniFit (S, M, L)	7028X/2X - Dual-size XL/2X	