

7086B

FlowTech LTE® 1D Standard Non-belted Full Body Harness, Tongue Buckle Leg Adjustment

Features :

- Lightweight Flowscape® shoulder yoke and sub-pelvic leg pads deliver evaporative breathability
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit
- Features lightweight forged aluminum alloy dorsal D-ring
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Quick-connect chest buckle features visual indicator showing positive connection
- Complies with ANSI Z359.11-2014



Material Specifications	
Webbing	Polyester; 5,000 lb min. static strength
D-ring	Aluminum alloy; 5,000 lb min. static strength
Buckles and Adjusters	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
CSA	Z259.10-2018
OSHA	1926.502 and 1910.66
ANSI	Z359.11-2014

Sizes & Part Numbers					
7086BS - Small	7086BM - Medium	7086BL - Large	7086BXL - XL	7086B2X - 2X	

