

7006B

Tradesman® Plus 1D Standard Non-belted Full Body Harness

Features :

- Features integral tri-layer padded shoulder yoke to provide breathable user comfort
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment
- Dorsal D-ring, quick connect chest, and mating buckle leg closures are all durably plated alloy steel
- Quick-connect buckle features visual indicators showing positive connection
- Complies with ANSI Z359.11-2014



Material Specifications		Performance Specifications		Compliant With:	
Webbing	Polyester; 5,000 lb min. static strength	Static Strength	3,600 lb min.	OSHA	1926.502 and 1910.66
D-rings	Plated alloy steel; 5,000 lb min. static strength	ANSI User Capacity	130 to 310 lb max.	CSA	Z259.10-2018
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength	OSHA User Capacity	130 to 425 lb max.	ANSI	Z359.11-2014

Sizes & Part Numbers					
7006BXS - XS	7006BSM - Dual-size Small/Med *	7006BLX - Dual-size Large/XL *	7006B2X - 2X	7006B3X - 3X	*Sizes that meet CSA Z259.10-2018 standard