

TILT N ROLL[®] LADDERS



- 4 STANDING HEIGHTS
- ALUMINUM
- 304 STAINLESS STEEL
- POWDER COATED STEEL



Cotterman Co.
 Division of Material Control, Inc.
 P.O. BOX 168 • 130 SELTZER RD. • CROSWELL, MI 48422
 810-679-4400 • FAX 810-679-4510
 TOLL FREE 800-5-LADDER
 www.cotterman.com info@cotterman.com



The TILTNROLL® features a special balanced design that allows it to tilt easily to the rolling position when pulled toward the user. The user is not required to extend a foot to assist in tilting the ladder to the rolling position. Once tilted, the ladder can be easily moved from job to job on the two 4" diameter wheels.

TILTNROLL® ladders are one-piece welded assemblies shipped ready to use. The ladders are supplied with handrails that extend 30" above the top step. They are designed to meet OSHA 1910 Subpart D, and ANSI A14.7 standards. Cal-OSHA models are also available. 59° climb angle.

SPECIFICATIONS AND PRICING

| CHOOSE FROM EXPANDED METAL, PERFORATED OR GRIP STRUT STEPS | NUMBER OF STEPS | TOP STEP HEIGHT | SINGLE TOP STEP | | | | DOUBLE TOP STEP | | | | |
|--|-----------------|-----------------|-----------------|------------|-----------|-------|-----------------|------------|-----------|-------|-------|
| | | | 16"Wx10"D | | 24"Wx10"D | | 16"Wx20"D | | 24"Wx20"D | | |
| | | | MODEL | BASE W"xL" | SHPG. WT. | PRICE | MODEL | BASE W"xL" | SHPG. WT. | PRICE | MODEL |

POWDER COATED STEEL: (450 LB. LOAD RATING) STANDARD COLOR: GRAY (AVAILABLE) SAFETY YL., ORANGE, DK. BROWN & BLACK.

| | | | | | | | | | | | | | | | | | | |
|--|---|-----|---------|-------|----|--|---------|-------|----|--|-----------|-------|----|--|-----------|-------|----|--|
| | 2 | 20" | 2TR18 | 20x24 | 38 | | 2TR26 | 28x24 | 43 | | 2TR18E4 | 20x34 | 49 | | 2TR26E4 | 28x34 | 60 | |
| | 3 | 30" | 3TR18 | 20x30 | 47 | | 3TR26 | 28x30 | 55 | | 3TR18E4 | 20x41 | 62 | | 3TR26E4 | 28x41 | 71 | |
| | 4 | 40" | 4TR18 | 20x37 | 58 | | 4TR26 | 28x37 | 66 | | 4TR18E4 | 20x47 | 72 | | 4TR26E4 | 28x47 | 83 | |
| | 5 | 50" | 5TR18 | 20x43 | 68 | | 5TR26 | 28x43 | 78 | | 5TR18E4 | 20x54 | 82 | | 5TR26E4 | 28x54 | 95 | |
| | | | | | | | | | | | | | | | | | | |
| | 2 | 20" | 2TR18A6 | 20x24 | 36 | | 2TR26A6 | 28x24 | 40 | | 2TR18E4A6 | 20x34 | 46 | | 2TR26E4A6 | 28x34 | 59 | |
| | 3 | 30" | 3TR18A6 | 20x30 | 45 | | 3TR26A6 | 28x30 | 51 | | 3TR18E4A6 | 20x41 | 60 | | 3TR26E4A6 | 28x41 | 69 | |
| | 4 | 40" | 4TR18A6 | 20x37 | 54 | | 4TR26A6 | 28x37 | 62 | | 4TR18E4A6 | 20x47 | 70 | | 4TR26E4A6 | 28x47 | 79 | |
| | 5 | 50" | 5TR18A6 | 20x43 | 64 | | 5TR26A6 | 28x43 | 73 | | 5TR18E4A6 | 20x54 | 79 | | 5TR26E4A6 | 28x54 | 90 | |
| | | | | | | | | | | | | | | | | | | |
| | 2 | 20" | 2TR18A3 | 20x24 | 36 | | 2TR26A3 | 28x24 | 40 | | 2TR18A3E4 | 20x34 | 49 | | 2TR26A3E4 | 28x34 | 56 | |
| | 3 | 30" | 3TR18A3 | 20x30 | 45 | | 3TR26A3 | 28x30 | 51 | | 3TR18A3E4 | 20x41 | 59 | | 3TR26A3E4 | 28x41 | 67 | |
| | 4 | 40" | 4TR18A3 | 20x37 | 55 | | 4TR26A3 | 28x37 | 62 | | 4TR18A3E4 | 20x47 | 68 | | 4TR26A3E4 | 28x47 | 78 | |
| | 5 | 50" | 5TR18A3 | 20x43 | 64 | | 5TR26A3 | 28x43 | 73 | | 5TR18A3E4 | 20x54 | 78 | | 5TR26A3E4 | 28x54 | 88 | |
| | | | | | | | | | | | | | | | | | | |

#304 STAINLESS STEEL: (450 LB. LOAD RATING) SAND BLASTED SATIN FINISH

| | | | | | | | | | | | | | | | | | | |
|--|---|-----|---------|-------|-----|--|---------|-------|-----|--|-----------|-------|-----|--|-----------|-------|-----|--|
| | 2 | 20" | 2TS18 | 20x24 | 54 | | 2TS26 | 28x24 | 59 | | 2TS18E4 | 20x34 | 68 | | 2TS26E4 | 28x34 | 75 | |
| | 3 | 30" | 3TS18 | 20x30 | 71 | | 3TS26 | 28x30 | 77 | | 3TS18E4 | 20x41 | 86 | | 3TS26E4 | 28x41 | 95 | |
| | 4 | 40" | 4TS18 | 20x37 | 88 | | 4TS26 | 28x37 | 97 | | 4TS18E4 | 20x47 | 103 | | 4TS26E4 | 28x47 | 113 | |
| | 5 | 50" | 5TS18 | 20x43 | 106 | | 5TS26 | 28x43 | 116 | | 5TS18E4 | 20x54 | 117 | | 5TS26E4 | 28x54 | 133 | |
| | | | | | | | | | | | | | | | | | | |
| | 2 | 20" | 2TS18A3 | 20x24 | 53 | | 2TS26A3 | 28x24 | 57 | | 2TS18A3E4 | 20x34 | 63 | | 2TS26A3E4 | 28x34 | 73 | |
| | 3 | 30" | 3TS18A3 | 20x30 | 70 | | 3TS26A3 | 28x30 | 76 | | 3TS18A3E4 | 20x41 | 83 | | 3TS26A3E4 | 28x41 | 91 | |
| | 4 | 40" | 4TS18A3 | 20x37 | 86 | | 4TS26A3 | 28x37 | 93 | | 4TS18A3E4 | 20x47 | 100 | | 4TS26A3E4 | 28x47 | 109 | |
| | 5 | 50" | 5TS18A3 | 20x43 | 104 | | 5TS26A3 | 28x43 | 112 | | 5TS18A3E4 | 20x54 | 118 | | 5TS26A3E4 | 28x54 | 127 | |
| | | | | | | | | | | | | | | | | | | |

ALUMINUM: (350 LB. LOAD RATING) 6061-T6 HIGH STRENGTH ALLOY

| | | | | | | | | | | | | | | | | | | |
|--|---|-----|---------|-------|----|--|---------|-------|----|--|-----------|-------|----|--|-----------|-------|----|--|
| | 2 | 20" | 2TA18A3 | 20x24 | 17 | | 2TA26A3 | 28x24 | 19 | | 2TA18A3E4 | 20x34 | 21 | | 2TA26A3E4 | 28x34 | 24 | |
| | 3 | 30" | 3TA18A3 | 20x30 | 23 | | 3TA26A3 | 28x30 | 24 | | 3TA18A3E4 | 20x41 | 26 | | 3TA26A3E4 | 28x41 | 30 | |
| | 4 | 40" | 4TA18A3 | 20x37 | 26 | | 4TA26A3 | 28x37 | 29 | | 4TA18A3E4 | 20x47 | 30 | | 4TA26A3E4 | 28x47 | 35 | |
| | 5 | 50" | 5TA18A3 | 20x43 | 30 | | 5TA26A3 | 28x43 | 34 | | 5TA18A3E4 | 20x54 | 35 | | 5TA26A3E4 | 28x54 | 40 | |
| | | | | | | | | | | | | | | | | | | |

Cotterman Co.

DIVISION OF MATERIAL CONTROL, INC.



"CHARGE IT"



MEMBER

SIA

MEMBER COMPANY

MHIA



National Safety Council

MEMBER ANSI

WARRANTY

All Cotterman products are guaranteed against defects in workmanship and materials for a period of one (1) year after shipment.

P.O. BOX 168
130 SELTZER RD.
CROSWELL, MI 48422

1-810-679-4400
FAX 810-679-4510
TOLL FREE 800-5-LADDER

F.O.B. FACTORY • TERMS: NET 30 DAYS
TAX NOT INCLUDED • PRICES SUBJECT TO CHANGE WITHOUT NOTICE