3M[™] DBI-SALA[®] Nano-Lok[™] for Hot Work Use Self-Retracting Lifelines



This SRL was tested to 8 calories, ensuring durability in applications like welding, grinding and torching. It is reinforced with Kevlar® fiber to withstand sparks, weld splatter and other high-heat exposure.

- 6 ft. (1.8 m) working length.
- Universal hot work icon to quickly and easily identify hot work product.
- 3M™ Connected Safety ID (CSID) equipped.



Selection guide:

	And	horage	type	Lifeline hook								
8	D		0	8	Compo			8	9			
	Single-Leg Interface	Twin-Leg Interface	Steel Carabiner	Steel Snap Hook	Steel Swiveling Snap Hook	Flat Steel Rebar Hook	Steel Rebar Hook with Loking Nose	Aluminum Captive Eye Carabiner	Aluminum Rebar Hook	Aluminum Rebar Hook with Locking Nose	9' Tie-Back	Part Number
	•											3101491
					•							3101492
	_											3101493
8 ft. Single Leg	•											3101494
ngle	•											3101495
t. Si												3101496
8										-		3101497
												3101498
	_										•	3101322
											-	3101324
		•		•								3101499
		1										3101500
eg G												3101501
8 ft. Twin Leg												3101502
f.												3101503
8		1							•			3101504
												3101505
												3101326