Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name or trade mark: Brilliant						
Supplier's address: Customer Service, Brilliantstraße 1, 27442 Gnarrenburg, DE Model identifier: G60773/93						
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type (or other electric interface)		/				
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
		General product p		I		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		22	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P _{on}), expressed in W		22,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82		
Outer dimen-	Height	2	Spectral power dis-	See image		
sions without separate con- trol gear, light- ing control	Width Depth	13 13	tribution in the range 250 nm to 800 nm, at full-load	in last page		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	150			
		Chromaticity coordi-	0,440			
		nates (x and y)	0,404			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,96			
the lumen maintenance factor	0,97					

(a)'-': not applicable; (b)'-': not applicable;

