## **Product Information Sheet**

Colour-tuneable light source:

High luminance light source:

Anti-glare shield:

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Brilliant  Supplier's address: Customer Service, Brilliantstraße 1, 27442 Gnarrenburg, DE							
Type of light source:							
Lighting technology used:	LED	Non-directional directional:	or	NDLS			
Light source cap-type	/						
(or other electric interface)							
Mains or non-mains:	NMLS	Connected I	ight	No			

## Product parameters

No

No

No

source (CLS):

Envelope:

Dimmable:

Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
<u> </u>	mption in on- 00 h), rounded st integer	31	Energy efficiency class	E			
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	3 800 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500			
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	31,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00			
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	84			
Outer dimen-	Height	1	Spectral power dis-	See image			
sions without	Width	575	tribution in the	in last page			
separate con- trol gear, light- ing control	Depth	7	range 250 nm to 800 nm, at full-load				

Yes

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	228			
		Chromaticity coordi-	0,323			
		nates (x and y)	0,342			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	13	Survival factor	0,96			
the lumen maintenance factor	0,97					

(a)'-': not applicable; (b)'-': not applicable;

