



**BS 5534:**

- All single-lap (interlocking) tiles must be mechanically fixed at least once with a nail or a clip
- All perimeter tiles must be mechanically fixed at least twice

**BS 8612:**

- Dry verge products must be fixed to a mechanical engagement on the face of the batten

**Features:**

- Manufactured from drawn UK produced, galvanised carbon steel
- Fully BS 5534:2014 compliant
- Single piece clip increases efficiency
- Does not foul drainage channel allowing free water passage
- Tested by BRE for wind resistance performance
- Suitable for approximately 90% of interlocking tile types in use

**CLIP 1**

Used for flat profile thin leading edge interlocking tiles and interlocking mock plain tiles



Product Code	Box Qty
RP1UTC1000	1000
RP1UTC200	200

**CLIP 2**

Used for flat profile standard interlocking tiles and most pan tiles



Product Code	Box Qty
RP2UTC1000	1000
RP2UTC200	200

**Universal Batten End Clip**



**Features:**

- Provides a secure fixing into the end grain
- Quick and easy to install
- Aluminium/zinc coating
- Meets BS 8612 requirements
- Nail grip feature secures the fixing

Product Code	Box Qty
RPUBEC50	50
RPUBEC10	10



# Tile Clip Compatibility

Manufacturer	Profile	Clip1 Flat Profile TLE Interlocking Interlocking Mock Plain Tile	Clip 2 Flat Profile STD Interlocking & Most Interlocking Pan Tiles
Forticrete	V2		✓
Forticrete	Gemini	✓	
Redland	49		✓
Redland	Double Pan		✓
Redland	Double Roman		✓
Redland	Mini Stonewold		✓
Redland	Richmond	✓	
Redland	Duo Plain	✓	
Marley	Ludlow Plus		✓
Marley	Major		✓
Marley	Wessex		✓
Marley	Mendip		✓
Marley	Double Roman		✓
Marley	Ashmore	✓	
Marley	Modern*		✓
Marley	Edgemere	✓	
Sandtoft	Standard		✓
Sandtoft	Double Pan		✓
Sandtoft	Double Roman		✓
Sandtoft	Calderdale*		✓
Sandtoft	TLE	✓	
Sandtoft	Cassius	✓	
Sandtoft	20/20	✓	
Russell	Pennine		✓
Russell	Argyll		✓
Russell	Double Roman		✓
Russell	Grampian		✓
Russell	Highland		✓