

TACWEAR[™]

BODY ARMOR & CARRIERS



FUSION SERIES





ALL THE PROPERTY OF THE PROPER

MODEL NUMBER: AFC-T2-959

THREAT 5 - 4



DEPARTMENT OF STATE ITAR / EAR: THIS DATA SHEET IS FOR AN EXPORT CONTROLLED PRODUCT. THE EXPORT OF TECHNICAL INFORMATION RELATED TO THIS PRODUCT IS GOVERNED BY THE U.S. DEPARTMENT OF STATE INTERNATIONAL TRAFC IN ARMS REGULATIONS (ITAR) OR THE DEPARTMENT OF COMMERCE EXPORT ADMINISTRATION REGULATIONS (EAR). THIS INFORMATION MUST NOT BE TRANSMITTED TO A FOREIGN PERSON/ENTITY WITHOUT PROPER AUTHORIZATION OF THE U.S. GOVERNMENT. VIOLATIONS MAY RESULT IN ADMINISTRATIVE, CIVIL, OR CRIMINAL PENALTIES. ITAR/EAR EXPORT LICENSES AND ITAR/EAR BROKERING AUTHORIZATION (AS APPROPRIATE) WILL BE REQUIRED PRIOR TO SUBMITTAL OF ANY FURTHER TECHNICAL INFORMATION AND/OR SHIPMENT OF SAMPLES AND/OR PRODUCTS.

- (AD) AREAL DENSITY: 0.89 psf
- $\langle \tau \rangle$ THICKNESS: 0.21"
- F FLEXIBILITY: High
- S TEMPLATE SIZES: NIJ C-1 through NIJ C-5
- PA PRODUCT APPLICATION:
 Concealable Body Armor, External Carriers,
 Plate Carriers, and Tactical Body armor
- TYPE OF MATERIALS:
 500D Twaron® Plain Weave
 Twaron® 4-Ply Unidirectional Fabric
- TYPE OF CONSTRUCTION:
 W.R.A.P.™ Water Repellent Armor
 Perimeter (Patent Pending)
- TYPE OF PROTECTIVE COVER:

 Brookwood 70D with Laminated Polyurethane
- TYPE OF PROTECTIVE SEAL:
 Sonobond Ultrasonic Bond
- AVAILABLE SHAPES AND GRADES:
 Available in ALL vest patterns as well as OEM
 Armor Specifications
- SPECIAL THREAT TESTING*:
 9mm V50: 1699 fps
 .357 Mag V50: 1632 fps
 FN SS197 40 grain V0
 Win SXT 9mm +P+ V0
 7.62x25 Tokarev 85 grain V0
 .357 SIG Win SXT 125 grain V0
 Corbon 9mm +P 90 grain V0

*Special Threat Testing Conducted in accordance with an abbreviated and modified NIJ 0101.06 and AFCI Special Threat Testing Protocol.




FUSION SERIES





MODEL NUMBER: AFC-T3A-525

THREAT



DEPARTMENT OF STATE ITAR / EAR: THIS DATA SHEET IS FOR AN EXPORT CONTROLLED PRODUCT. THE EXPORT OF TECHNICAL INFORMATION RELATED TO THIS PRODUCT IS GOVERNED BY THE U.S. DEPARTMENT OF STATE INTERNATIONAL TRAFC IN ARMS REGULATIONS (ITAR) OR THE DEPARTMENT OF COMMERCE EXPORT ADMINISTRATION REGULATIONS (EAR). THIS INFORMATION MUST NOT BE TRANSMITTED TO A FOREIGN PERSON/ENTITY WITHOUT PROPER AUTHORIZATION OF THE U.S. GOVERNMENT. VIOLATIONS MAY RESULT IN ADMINISTRATIVE, CIVIL, OR CRIMINAL PENALTIES. ITAR/EAR EXPORT LICENSES AND ITAR/EAR BROKERING AUTHORIZATION (AS APPROPRIATE) WILL BE REQUIRED PRIOR TO SUBMITTAL OF ANY FURTHER TECHNICAL INFORMATION AND/OR SHIPMENT OF SAMPLES AND/OR PRODUCTS.

- AREAL DENSITY: 1.17 psf
- 0.275" THICKNESS:
- High FLEXIBILITY:
- TEMPLATE SIZES: NIJ C-1 through NIJ C-5
- PRODUCT APPLICATION: PA Concealable Body Armor, External Carriers, Plate Carriers, and Tactical Body armor
- TYPE OF MATERIALS: 3000D Twaron® Microlam Twaron® 2-Ply Unidirectional Fabric
- TYPE OF CONSTRUCTION: W.R.A.P.™ – Water Repellent Armor Perimeter (Patent Pending)
- TYPE OF PROTECTIVE COVER: PC Brookwood 70D with Laminated Polyurethane
- TYPE OF PROTECTIVE SEAL: PS Sonobond Ultrasonic Bond
- **AVAILABLE SHAPES AND GRADES:** (SG) Available in ALL vest patterns as well as OEM **Armor Specifications**
- **SPECIAL THREAT TESTING*:** 2 grain RCC V50: 3013 fps FN SS197 40 grain V0 4 grain RCC V50: 2545 fps Win SXT 9mm +P+ V0 16 grain RCC V50: 2225 fps 7.62x25 Tokarev 85 grain V0

.44 Mag V50: 1615 fps .357 Sig V50: 1735 fps

Speer GD .357 Mag VO

*Special Threat Testing Conducted in accordance with an abbreviated and modified NIJ 0101.06 and AFCI Special Threat Testing Protocol.




PIONEER









NIJ 0101.04

NIJ THREAT LEVEL: $\langle \mathsf{TL}
angle$

1.20 LBS/FT **WEIGHT:**

0.27" THINNESS:

LAYER COUNT: 10

BALLISTIC MATERIAL: 3000D Micro-Laminate

PIONEER IIIA



NIJ 0101.04

NIJ THREAT LEVEL: IIIA

1.56 LBS/FT **WEIGHT:** $\langle \mathbf{w} \rangle$

0.35" THINNESS:

LAYER COUNT: 13

BALLISTIC MATERIAL: 3000D Micro-Laminate



THEMIS






AVIED

MODEL NUMBER: D1871





DEPARTMENT OF STATE ITAR / EAR: THIS DATA SHEET IS FOR AN EXPORT CONTROLLED PRODUCT. THE EXPORT OF TECHNICAL INFORMATION RELATED TO THIS PRODUCT IS GOVERNED BY THE U.S. DEPARTMENT OF STATE INTERNATIONAL TRAFC IN ARMS REGULATIONS (ITAR) OR THE DEPARTMENT OF COMMERCE EXPORT ADMINISTRATION REGULATIONS (EAR). THIS INFORMATION MUST NOT BE TRANSMITTED TO A FOREIGN PERSON/ENTITY WITHOUT PROPER AUTHORIZATION OF THE U.S. GOVERNMENT. VIOLATIONS MAY RESULT IN ADMINISTRATIVE, CIVIL, OR CRIMINAL PENALTIES. ITAR/EAR EXPORT LICENSES AND ITAR/EAR BROKERING AUTHORIZATION (AS APPROPRIATE) WILL BE REQUIRED PRIOR TO SUBMITTAL OF ANY FURTHER TECHNICAL INFORMATION AND/OR SHIPMENT OF SAMPLES AND/OR PRODUCTS.

- (AD) AREAL DENSITY: 0.87 DSf
- $\langle \tau \rangle$ THICKNESS: 0.20"
- F FLEXIBILITY: Medium
- \langle **S** \rangle **TEMPLATE SIZES:** NIJ C-1 through NIJ C-5
- PA PRODUCT APPLICATION:
 Concealable Body Armor, External Carriers,
 Plate Carriers, and Tactical Body armor
- M TYPE OF MATERIALS:
 100% UDPE DSM Dyneema
- TYPE OF CONSTRUCTION:
 Tack and Bottom Seal
- TYPE OF PROTECTIVE COVER:

 Brookwood Nylon with Laminated Polyurethane
- PS TYPE OF PROTECTIVE SEAL: Sonobond Ultrasonic Bond
- AVAILABLE SHAPES AND GRADES:
 Available in ALL vest patterns as well as OEM
 Armor Specifications
- SPECIAL THREAT TESTING*:

 2 grain RCC V50: 3033 fps

 4 grain RCC V50: 2624 fps

 16 grain RCC V50: 2226 fps

 64 grain RCC V50: 1778 fps

 17 grain FSP V50: 2087 fps

 .44 Mag V50: 1747 fps

 .357 Siq V50: 1917 fps

*Special Threat Testing Conducted in accordance with an abbreviated and modified NIJ 0101.06 and AFCI Special Threat Testing Protocol.



SPIKESHANK



NIJ THREAT LEVEL: SPIKE 1

WEIGHT: W

.32 LBS/FT

THINNESS:

.09" (2.3 mm)

LAYER COUNT: 10

BALLISTIC MATERIAL: Kevlar PRIMO



SPIKESHANK

NIJ 0115.00

USA MADE

NIJ THREAT LEVEL: SPIKE 2

WEIGHT:

.45 LBS/FT

THINNESS:

.12" (3.0 mm)

LAYER COUNT: 14

BALLISTIC MATERIAL: Kevlar PRIMO

MODEL NUMBER: AFC-S2-K14

SPIKESHANK

USA MADE

NIJ THREAT LEVEL: SPIKE 3

WEIGHT:

.65 LBS/FT

THINNESS:

.17" (4.3 mm)

LAYER COUNT: 20

BALLISTIC MATERIAL: Kevlar PRIMO



BALLISTIC BARRIER BLANKET



NIJ 0108.01

SERIES: $\langle s \rangle$

Fusion

TL

NIJ THREAT LEVEL: IIIA

 $\langle \mathbf{w} \rangle$

WEIGHT:

18.72 oz.

T

THINNESS:

0.30" (7.62 mm)

LAYER COUNT: 30

SIZE: Standard size for the barrier blanket is 4' x 6'. However, other sizes are available including, but not limited to, 5' x 6', 6' x 6',

and custom designs.



WOVEN ARAMID (to desired specs)



Woven BB

NIJ THREAT LEVEL: IIIA (TL)

15.99 nz. W **WEIGHT:**

.30" (7.62 mm) (T THINNESS:

LAYER COUNT: 17

BALLISTIC MATERIAL: Woven Aramid (or others available)

> **SIZE:** Standard size for the barrier blanket is 4' x 6'. However, other sizes are available including, but not limited to, 5' x 6', 6' x 6', and custom designs.





NIJ 0108.01



USA MADE

PLATES

TRAUMA PLATES + LEVEL III AND III PLUS PLATES IN CONJUNCTION WITH (ICW) SOLUTION





- + IIIA trauma Plates
- + 5x7 | 5x8 | 6X8 | 7X9 | 8X10 | 10X12
- + III+SA Rifle Threat Plate
- + IVSA Rifle Threat Plate







MODEL NUMBER: AFC-RF2-3CE

NIJ 0101.06







7.62 x 51 MBO BALL NIJ CERTIFIED:

1.1" THICKNESS:

5.4 lbs **WEIGHT:** W

SIZE: 10" x 12"

PA PRODUCT APPLICATION:

Concealable Body Armor, External Carriers, Plate Carriers, and Tactical Body armor

MULTI-HIT M

(ST) NIJ SPECIAL THREATS TESTED:

5.56 x 45 M193 @ 3100-3150 fps 7.62 x 39 M67 @ 2880-2930fps 7.62 x 63 JSP @ 2730-2780 fps 5.56 x 45 M855 @ 3100-3150 fps 7.62 x 39 M43 @ 2340-2390 fps 7.62 x 54r LPS @ 2800-2850 fps

BALLISTIC HELMET

HIGH-CUT MICH IIIA



NIJ 0106.01



1150_{cm²} - 1250_{cm²} **BALLISTIC AREA:** (BA)

NIJ THREAT LEVEL: IIIA TL

2.87 LBS (Includes Accessories) W WEIGHT:

MIL SIZE:

MATERIAL: Laminate Reinforced Aramid / Impregnated with phenolic resin

SHAPE: High-Cut MICH with Picatinny Rail and Mount System

COLORS: Black, Khaki, Olive Green, UN Blue

BALLISTIC HELMET PASGT

MODEL NUMBER: H-PASGT-3A



NIJ 0106.01

1150_{cm²} - 1250_{cm²} **BALLISTIC AREA:**

NIJ THREAT LEVEL: IIIA

3.2 LBS (Includes Accessories) WEIGHT:

SIMILIXL SIZE:

MATERIAL: Aramid Fiber / Impregnated with phenolic

SHAPE: PASGT

COLORS: Black, Khaki, Olive Green, UN Blue



SHIELDS

IIIA







- **D DETAILS:** Flat or single curve weapon mount design with exclusive contoured apron designated to allow better transitioning through narrow spaces such as bus, airline and train aisles while still maintaining a large area of torso protection.
- **E EXCLUSIVE** contour molded patent pending forearm pad provides improved lateral stability. Stabilizing forearm strap.
- O OPTIONAL LED light kits available
- **S SIZES:** Compact 18" x 30", Entry 24" x 36", Entry 24" x 48"
- **c COLORS:** Urban Gray, Carbon, Black, Coyote and, Ranger Green













USA MADE *

CONCEALABLE

CARRIERS



FEATURES:

- 1 Fully adjustable shoulders
- 2 Large straps for adjustability
- **3** Available with NIJ.06 Level II or IIIA ballistics
- **4** Dual plate pocket accommodates 5"x 8" 8"x 10" trauma inserts
- **5** Spacer mesh inner lining to keep you cool and dry
- **6** Custom sizing or standard sizing available

HYBRID CARRIER



T-SHIRT CARRIER



TACTICAL







FEATURES:

- 1 Fully adjustable shoulders
- 2 Optional shoulder and neck protection
- **3** Optional bi-ceps protection
- 4 Large id patch area
- **5** Fully adjustable front cumber bun
- **6** Built in side protection plate pockets
- 7 Helmet profiled neck protection
- 8 Large officer down strap
- **9** Open top for quick plate removal

LASER CUT VEST







QUICK RELEASE VEST







ASPETTO CLIP



FEATURES:

- 1 Can be quickly adapted to most front opening tactical vests with retro fit kit
- **2** Aspetto clip allows for quick release capability for almost any tactical outer carrier without creating a gap with ballistic coverage
- **3** Colors: Black- Ranger Green-Coyote
- 4 Channel/Lock System Tensile: > 300lbs MOLLE Compatible
- **5** Berry amendment compliant (Made in USA)
- **6** 18 month warranty for manufacturing defects





TACWEAR[™]

This catalog provides a brief summary of the capabilities of Tac Wear™ USA. We can provide the armor carriers solutions displayed here as well as customized solutions for your particular department, agency, or security need.

Please contact us at usasales@tacwear.com or call us at 888-TAC-WEAR (822-9327).

www.tacwearusa.com



Tac Wear™ USA PO Box 543 Marietta, GA 30061 888-TAC-WEAR (822-9327) www.tacwearusa.com