# KAMINUS





# F30 SQUARE

Designed according to the more recent and restrictive european normatives concerning manufacturing and safety, this product represents the top of technology achieved after 50 years of experience in the production of wood boilers and central heating cookers. Connected to a central heating system the Bosky F30 Square warms your entire house, furnishing it with style thanks to painstaking trimmings. Equipped with a Ceran glass ceramic hob and enamelled oven it will serve as your winter stove.

## Dimensions

Depth

#### Overall Width 1062mm 918/968mm Height Depth 710mm Weight 310kg Firebox Opening Width 224mm 282mm Height Firebox Internal Dimensions Width 300mm Height 540mm Depth 442mm Oven Internal Dimensions Width 360mm Height 320mm

## **Special Features**

- $\bullet$  Nominal output: 17.9kW-N / 10.2 kW-H<sub>2</sub>O (EUROPEAN)\*
- 12 Litre 3 Bar hydronic water tank
- •63 Litre panoramic enamelled oven
- Brushed steel cooking plate with optional cast iron rings
- Optional CERAN® glass ceramic hob
- Automatic draft control
- Enamelled oven complete with grill and dripping pan
- Grate adjustment lever
- •Oven temperature control by smoke flap
- Wood storage pan
- Efficiency: Up to 88.2% (EUROPEAN)\*
- Wood consumption: 4.7kg/hr @ medium burn rate



550mm













### Bosky "Ready to Start" Line

The Bosky "Ready to Start" line of hydronic cookers give you the ability to easily connect your cooker to the home hydronic system. The standard equipment that makes this possible is the inclusion of the Circulator, Safety Valve, Safety Exchanger and the Expansion Tank for closed vessel installations. This can be used to heat radiators, flooring, towel racks, swimming pools and hot water for your house depending on how your hydronic system in configured. The Bosky line of products are the ideal solution to face the winter in tranquillity exploiting a maximum heat yield through your entire home with minimal energy consumption all while you cook your families favourite meal.

# Flue Specifications

Diameter

Centre of flue to rear of fire	149mm
Clearances Combustible Rear Wall	
Side Clearance	300mm
Rear Clearance	300mm
Front Clearance	800mm
Front Hearth	500mm
Min. Hearth Width	1100mm

#### XXL

150mm

The strict manufacturing standards and the high quality of raw materials, grant higher heat accumulation and stable durability of the fire box and other components.

### Easy Cleaning

The wide ash pan and the obvious inspection points make maintenance easier keeping the efficiency of the firebox at its highest levels.

## Smoke By-Pass

Smoke by-pass technology reduces smoke entering the living zone with every wood load by redirecting exhaust to the rear of the fireplaces using the sliding conrtol.

#### Enamelled Oven

Enamelled oved complete with grill and dripping pan.

#### Hot Plate

Incorporates practicality and hygiene with the easy to clean hotplate to heat your food.

The manufacturer reserves the right to make changes without previouis notice.