



Dante

The La Nordica Dante is a beautifully designed fireplace with a selection of benches to bring a sense of style and convenient heat to your home. The Nordiker Firebox is practical, silent, ecological and it enables heating wide areas in very short amounts of time. The Dante has a nominal power output of 8.9kW and a peak output of 13.0kW that meets the latest “benchmark” German certification standards as well as Australian standards.

Dimensions

Overall

Width	822mm
Height	1055/1480mm
Depth	550mm
Weight	158/183kg

Firebox Opening

Width	626mm
Height	278mm

Firebox Internal Dimensions

Width	652mm
Height	327mm
Depth	350mm

Flue Specifications

Diameter, adapter inc.	160mm
Centre of flue to rear of fire	244mm

Special Features

- Output: Nominal **8.9kW**, Peak **13.0kW**
- Extractable ash drawer
- Cast Iron Grid and Door G20
- Nordiker Firebox
- Reversible door opening
- Multiple stand configurations
- Adjustable primary and secondary air
- Pre-calibrated tertiary with post combustion system
- Particle emissions: **1.1g/kg**
- Efficiency: **61%** (AS/NZS4012/4013), **85.5%** (EUROPEAN)*
- Wood consumption: **2kg/hr @** medium burn rate





Clearances

Combustible Rear Wall

Rear Clearance	475mm
Rear Clearance with Shield	250mm
Side Clearance	575mm

Front Hearth	500mm
Min. Hearth Width	1050mm

Combustible Corner Wall

Corner Clearance	250mm
------------------	-------

Certification

- AS/NZS 4012/4013 (2014) (Australia)
- 15a B-VG (Austria)
- BlmSchV (Germany)
- Flamme VERTE Le Label du chauffage au bois (France)
- D.M. 186/2017 4 Stars

***IMPORTANT NOTE:** According to the AS/NZS 4012/4013 efficiency, 9 logs (12.9Kg) were used for testing. The manufacturers recommendation is 3-4 logs (3-4Kg) which will result in higher efficiency and less wood used while achieving same heat output.

BBC Bring Back Breath into Combustion

Air intake system that takes combustion fresh air from the outside leading it directly into the appliance.

CGC Clean Glass Control

A System to preheated air which removes any deposits from forming on the hearth door glass.

PCS Post Combustion System

The combustion system developed by La Nordica allows, due to a secondary/tertiary air system, a post combustion which significantly reduces emissions.

RDT Resistant Door at the Time

La Nordica-Extraflame appliances doors are manufactured in high quality cast iron.

Nordiker®

La Nordica uses a special patented highly resistant material allowing very high combustion temperatures, resulting in higher efficiency and lower emissions.

For more information
please contact us or visit our website
ph: 03 9028 2637
e: info@kaminus.com.au
www.kaminus.com.au

